

Project		Catalog #		Type	
Prepared by		Notes		Date	



Fail-Safe

UC1

Undercabinet, 3/4" depth
3 lengths: 24" / 36" / 48"
Anti-microbial finish standard
CCT selectable

Typical Applications
Healthcare • Patient rooms • Exam & procedure rooms • Nurse stations • Schools • Labs • Pharmacies

Interactive Menu

- Dimensional and Mounting Details [page 2](#)
- Accessories [page 2](#)
- Energy Data [page 3](#)
- Product Specifications [page 3](#)
- Product Warranty

Product Certification

Product Features


Top Product Features

- 3/4" depth to fit discretely in a variety of spaces
- Anti-microbial white paint finish, standard
- Available in 24", 36", and 48" lengths
- IK10 rated for maximum impact resistance
- 90 CRI standard
- Selectable color temperatures of 2700K, 3000K, 3500K, 4000K, and 5000K - for use in multiple applications
- Field installed motion sensor
- Universal voltage operates at 120V - 277V
- Continuous dimming to 5% at 120V (ELV/Triac) - 120V

Order Information

Sample number: UC1-24=24" Undercabinet
UC1-48=48" Undercabinet

Family	Length
UC1=Under Cabinet, Nominal 1" Deep, Anti-microbial White	24=24 inch 36=36 inch 48=48 inch






Dimensional and Mounting Details

Mounting Height H (ft)	Maximum PIR Detection Distance ^A X (ft)
2	3.5
4	5.7
6	6.5

^A Actual detection distance may vary based on multiple factors including but not limited to angle of moving object and reflectivity of surrounding surfaces. Table is provided for guidance purposes only.

Size	24 in. Nominal	36 in. Nominal	48 in. Nominal
Length	23.98" [609.1mm]	32.44" [824mm]	47.18" [1,198.4mm]



Accessories

Size Description	24 in. Nominal	36 in. Nominal	48 in. Nominal
Length "L"	23.98" [609.1mm]	32.44" [824mm]	47.18" [1,198.4mm]
Wattage*	9.4	12.7	17.3
Lumens*	670	915	1275
Efficacy - LPW*	71	72	74
Nominal Lumens/ft	335	305	319


* At factory setting of 3000K for white fixtures, check Photometric data for individual specifications

** At 120V only w/o Accessory


	UC1 Series
Power Factor**	>0.98
THD**	<20%
Color Rendering Index (CRI)	>90

HU30MUNVMSP Motion Sensor Module

Note: Can be purchased separately (HU30MUNVMSP).



Connectors & Accessories



HU101
3" Daisy Chain Connector



HU102
6" Daisy Chain Connector



HU1010
12" Daisy Chain Connector




HU1011
18" Daisy Chain Connector




HU103
24" Daisy Chain Connector



HU104
120" Daisy Chain Connector



HU115
48" Power Cord - 120V only



HU109
Splice Box



HU107
1-1/2" Male-to-Male Connector

Finish: P=White **Example:** HU101P=3" Daisy Chain Connector, White



Energy Data

Catalog	CCT (K)	Lumen	Efficacy (lm/W)	Watt (W)	PF	CRI	R9
UC1-24 (24" Length)	2700	670	73	9.15	0.964	93.8	60.5
	3000	681	74	9.15	0.964	94.7	68.0
	3500	692	75	9.16	0.965	95.1	74.1
	4000	702	76	9.17	0.965	94.8	77.7
	5000	715	78	9.16	0.965	92.5	72.8
UC1-36 (36" Length)	2700	920	74	12.43	0.968	93.8	61.0
	3000	931	74	12.46	0.969	94.8	68.5
	3500	947	75	12.47	0.969	95.2	74.6
	4000	963	77	12.48	0.969	94.9	78.2
	5000	984	78	12.49	0.969	92.5	73.2
UC1-48 (48" Length)	2700	1279	76	16.81	0.981	93.8	61.1
	3000	1301	77	16.82	0.981	94.8	68.6
	3500	1393	82	16.82	0.981	95.2	74.7
	4000	1343	79	16.83	0.981	94.9	78.3
	5000	1370	81	16.82	0.981	92.5	73.3

Product Specifications

Even Light Distribution

- Specialized optical system consisting of tightly clustered proximity phosphor LEDs, advanced optical chamber coatings and lens materials resulting in soft illumination with high efficiency.
- These fixtures are ideal for task lighting over glossy surfaces with no distracting shadow patterns

Color Temperature

6 Position external selector which includes a 5 CCT SeleCCTable color temperature switch that allows users to choose between 2700K, 3000K, 3500K, 4000K and 5000K, and an additional Dim-To-Warm setting (D2W range: 2700K to 1800K at 120V), for the customer's lighting need

PIR Motion Sensor Module

- Offered as a field installable modular accessory, the PIR technology based motion sensor allows for the fixture on/off to be managed based on movement detection. The UC1 PIR sensor works as an occupancy/vacancy sensor which activates the fixture when motion is detected and turns off the fixture when no motion is detected for 8 continuous minutes

Wiring Flexibility

User can power a fixture with multiple options: (See installation instructions for more details)

- Flexible conduit or romex can be used directly to either end of back of any size fixture to power the fixtures. Conduit connector and romex strain relief hardware are included with each fixture
- Plug in cord (sold separately) can be utilized to link additional fixtures to the circuit. (120V only)

User can wire multiple fixtures with different options: (See installation instructions for more details)

- Wiring multiple fixtures can be done using flexible conduit or romex directly to either end of back of any size fixture. Conduit connector and romex strain relief hardware are included with each fixture
- Plug in connectors (sold separately) can be utilized to link additional fixtures to the circuit
- Link any combination of fixtures up to 440W total load using available wiring options

Durable Low Profile Housing

Extruded aluminum housing and color matched end caps with a sleek over all height of 3/4"

Mounting

Each unit is secured directly to the mounting surface with just two fasteners keeping installation costs and efforts low. Can be mounted in horizontal and vertical orientations

Optional Accessories

- PIR Motion sensor and optional splice box are accessories offered for the series. The optional splice box has a connection port on each side to allow for runs in either or both directions. Includes Romex/ 1/2" conduit connector
- Various connector cable options and lengths provide flexibility of mounting location

Finish Options

Fixtures are available with a white antimicrobial finish

Electronic Driver & Dimming

- Universal Voltage (120-277V, 50/60Hz) Electronic driver provides flicker free light output and noise free operation
- Universal Voltage electronic driver is controlled with an integral on/off switch
- Designed for continuous dimming (ELV or TRIAC) down to 5% at 120V with compatible dimmers

Compliance & Certifications

- UL Certified
- Can be used to meet IECC, ASHRAE commercial standards
- FCC rated driver
- Can be used for State of California Title 24 high efficacy LED compliance under JA8
- Damp location listed
- IK10 rated for maximum impact resistance

Factory Defaults

The fixtures will be set to the following default where applicable:

- CCT: 3000K

Warranty

Five-year limited warranty, consult website for details www.cooperlighting.com

* See our website for dimming guidance information. www.cooperlighting.com