

# Specifications



Photo is representative



## Eaton V28M48T45CUEE

Eaton General purpose ventilated transformer, DT-3 (3-phase), PV 208 x 120V, Taps: 2 at +2.5% /4 at -2.5%, SV 480 delta, 150°C rise w/ 200°C insulation system, 45 kVA, Copper windings, EE

### General specifications

<b>PRODUCT NAME</b>	Eaton General purpose ventilated transformer
<b>CATALOG NUMBER</b>	V28M48T45CUEE
<b>UPC</b>	786680098772
<b>PRODUCT LENGTH/DEPTH</b>	16.5 in
<b>PRODUCT HEIGHT</b>	30 in
<b>PRODUCT WIDTH</b>	23 in
<b>PRODUCT WEIGHT</b>	482 lb
<b>WARRANTY</b>	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
<b>COMPLIANCES</b>	NEMA TP-1 Compliant
<b>CERTIFICATIONS</b>	UL Listed
<b>CATALOG NOTES</b>	NEMA TP-1 efficient

## Physical Attributes

COIL MATERIAL	Copper
FRAME	912B
TAP SIZE	2 at +2.5% FCAN, 4 at -2.5% FCBN
TYPE	Dry Type Distribution Transformer

## Performance Ratings

FREQUENCY RATING	60 Hz
PRIMARY VOLTAGE	208 x 120 V
SECONDARY VOLTAGE	480 delta
TEMPERATURE RISE	150 °C rise
VOLT AMPERE RATING	45 kVA

## Miscellaneous

WEATHERSHIELD	WS38
---------------	------

## Resources

CATALOGS	<a href="#">Commercial Distribution, Transformers, Volume 2, Tab 2</a>
SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton Specification Sheet - V28M48T45CUEE</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

