

60405

UPC: 08593760405
 UNSPSC: 31162101
 Standard Qty: 100
 Master Carton Qty: 1000
 Country of Origin: CHINA



3/8-16" Shallow Embedment Steel Drop-In Anchor, Includes Setting Tool, Zinc Plated

Product Attributes

| | |
|-----------------------------|--|
| Brand Name | Minerallac |
| Sub Brand | Cully |
| Type | Steel Drop-In Anchor |
| Special Features | Shallow Embedment Anchor |
| Size | 3/8"-16 |
| Diameter | 0.375" |
| Minimum Embedment Depth | 0.750" |
| Thread Type | Internal Threads |
| Thread per Inch | 16 |
| Drill Size | 1/2" |
| Material | Steel |
| Finish | Zinc Plated |
| Type | Mini Dropin expansion anchor |
| Application | A carbon steel machine bolt anchor designed for use in shallow embedment applications. |
| Material | Zinc Plated Carbon Steel |
| Suitable Base Materials | Normal Weight Concrete, Lightweight Concrete, Precast Hollow Core Plank, and Concrete Over Steel Deck |
| Benefits/ Features | Internally threaded anchor for easy bolt removability and service work, ideal for precast hollow core plank and post-tensioned concrete slabs, lip provides flush installation and consistent embedment, Manual setting tool scores flange when set to verify proper expansion depth |
| Rod/ Anchor Diameter | 3/8" |
| Outside Diameter | 1/2" |
| Overall Length | 3/4" |
| Minimum Embedment Depth in. | 3/4" |

Compliance Information

Buy America Act Compliant: No
 Buy American Act Compliant: No
 RoHS Compliant: Yes
 UL Compliant:
 UL Code:

Proposition 65

This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.

Minerallac Company

Tel: 800-927-3293
 Fax: 800-824-8942
www.minerallac.com

60405

UPC: 08593760405

UNSPSC: 31162101

Standard Qty: 100

Master Carton Qty: 1000

Country of Origin: CHINA



3/8-16" Shallow Embedment Steel Drop-In Anchor, Includes Setting Tool, Zinc Plated

| | |
|---|-----------|
| Ultimate Tension Strength (3,000 PSI) | 1,980 lbs |
| Ultimate Shear Strength (3,000 PSI) | 2,700 lbs |
| Allowable Tension Strength (3,000 PSI) | 495 lbs |
| Allowable Shear Strength (3,000 PSI) | 675 lbs |

WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.