

PVC Coated Elbows

Catalog Number: EL-050X90

UPC: 736953002937



Description

1/2X90 PVC Coated Standard Elbow

Factory-bent PVC coated elbows are more accurate, quicker to install and more economical because they eliminate field bending time and waste of material. Electrical continuity is maintained across assembled joints.

Application

- Factory-bent for accurate, quicker to install and eliminates costly field bending and waste of material
- Factory-bent for accurate, quicker to install and eliminates costly field bending and waste of material

Features


- 12 trade sizes from 1/2" through 6"
- 2 mil green urethane interior coating
- 40 mil gray PVC exterior coating
- Available in standard sizes 90°, 60°, 45°, 30° bends
- Color-coded thread protector caps for quick identification of conduit size

General

| | |
|-------------------------|---|
| Exterior Finish: | A nominal .040 inch (40 mil) gray PVC coating |
| Interior Finish: | A nominal .002 inch (2 mil) green urethane |
| Material: | STEEL |
| Thread Finish: | A green urethane coating over steel |
| Thread Protector Color: | Black |

Dimensions

| | |
|------------------------------|--------|
| Metric Size Designators | 16 |
| Nipple Length (Inches) | 11-1/4 |
| Diameter - External (Inches) | 0.92 |
| Diameter - Internal (Inches) | 0.632 |
| Radius A (Inches) | 3.79 |
| Radius B - Standard (Inches) | 4.25 |
| Radius C (Inches) | 4.71 |
| Offset D (Inches) | 6.04 |
| Offset E (Inches) | 6.5 |
| Offset F (Inches) | 12.615 |
| Tangent (Inches) | 2.25 |



PVC Coated Elbows

Catalog Number: EL-050X90

UPC: 736953002937



Technical / Specification Documents

| | |
|-----------------------------------|----------------------|
| Specification Guide (1995 Master) | AVAILABLE ON WEBSITE |
| Specification Guide (2004 Master) | AVAILABLE ON WEBSITE |
| Installer Certification and Tools | AVAILABLE ON WEBSITE |
| Chemical Resistance Charts | AVAILABLE ON WEBSITE |
| Performance Specifications | AVAILABLE ON WEBSITE |

Standards

| | |
|----------------|--------------|
| UL 6: | E2314 |
| CSA Certified: | C22.2 No. 45 |

Notes

Both PVC and zinc coatings have been investigated as primary protection against corrosion.

Restricted for use with threaded fittings only.