



Color: **N/A** Light Almond

UPC Code: 07847772776

Country Of Origin: Mexico

NEMA:
5-15R



GFNT1-HFT

Item Description

SmartlockPro GFCI Duplex Receptacle Outlet, Extra Heavy-Duty Hospital Grade, Wallplate Included, Power Indication, NAFTA Compliant, 15 Amp, 20 Amp Feed-Through, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Light Almond

Technical Information

AC Horsepower Ratings

At Rated Voltage: 1 HP

Electrical Specifications

Grounding: Self-Grounding

Pole: 2

Short Circuit Current Rating: 10kA

Wire: 3

Amperage: 15 A & 20 A Feed-Through

Voltage: 125 VAC

Environmental Specifications

Flammability: Rated V-0 per UL 94

Operating Temperature: -35C to +66C

Material Specifications

Body Material: Polycarbonate

Face Material: PBT

Ground Clips: Brass

Grounding Screw: Plated Steel

Line Contacts: Brass

Strap Material: Galvanized Steel

Terminal Clamp: Brass

Terminal Screws: Plated Steel

Mechanical Specifications

Product ID: Ratings are permanently marked on device

Terminal Accom.: 14-10 AWG solid or stranded

Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Termination: Back or Side Wire

Product Features

Color: Light Almond

NEMA: 5-15R

Brand: SmartlockPro

Function: GFCI

Device Type: Duplex Receptacle Outlet

Grade: Extra Heavy-Duty Hospital Grade

Feature: Wallplate Included

Feature 3: Power Indication

Feature 4: NAFTA Compliant

Standards and Certifications

ANSI: C-73

Applicable Standards: UL 943, UL 498, CSA C22.2 No. 42 & 144, FedSpec W-C-596

Certification/Listing: UL, CSA, NOM-ANCE

NEMA: WD-1 & WD-6


Warranty

Product Warranty: 2-Year Limited

Patents*

CA2341552	US6657834
CA2358721	US6788173
CA2425810	US6864766
CA2427366	US6944001
CA2515035	US7336458
MX234458	US7400479
MX251584	US7463124
MX269232	US7697252
MX276411	US7737809
MX276626	US7764151
MX302458	US7907371
MX308495	US8004804
MX315596	US8054595
US6040967	US8130480
US6246558	US8547126
US6282070	US8587914
US6381112	US8599522
US6437953	US9053886
US6646838	US9077091

*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.



SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Téléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts/

