



UPC Code: 07847781461
Country Of Origin: Mexico

LB115-DF

Brand Features

Leviton Circuit Breakers provide overload and short-circuit protection and feature an all plug-on design. AFCI/GFCI circuit breakers offer protection both from electrical fires that could result from arc-faults and from electrical shock due to ground faults in one smart device. All hot and neutral wires terminate at custom lugs in the panel, not at the circuit breaker*, so the entire panel can be wired at rough-in without circuit breakers installed. Branch circuit breakers are easily plugged-on at final installation. Circuit breakers also feature color indicators in the handle to easily see operational status ata-glance.

*For applications up to 60A when using copper wire; or 50A when using aluminum wire

RoHS: Yes

UL1699.A: Yes

Item Description

Branch Circuit Breaker, AFCI/GFCI 1-Pole 15A 120V, 10Ka Interrupt Rating

Technical Information

Product Features
Operating Temperature: -40°C to 85°C

Electrical Specifications

Amnuscrae: 45 Amnu

Amperage: 15 A
Pole: 1

Short Circuit Current Rating: 10 KA

Type: AFCI/GFCI UL 489: Yes Voltage: 120 VAC UL 943: Yes

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747
Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

