



busbar adapter 60 mm SYS. UL 508 Busbar system 60 mm Bar  
thickness: TT profile UL rating 240-600V/540A Can be used in spring  
circuits for 3VL circuit breaker with pipe contacting for cable outlet  
top/bottom Adapter length 296 mm Adapter width 140 mm for VL400  
UL, JG-FRAME for VL400X UL, LG-FRAME

| Model                                   |                |
|-----------------------------------------|----------------|
| Product brand name                      | SETRON         |
| Product designation                     | Device adapter |
| Design of the product                   | Accessories    |
| Current / at AC / rated value           | 400 A          |
| Operating voltage / at AC / rated value | 690 V          |
| Width                                   | 140 mm         |
| Busbar center-to-center spacing         | 60 mm          |
| Net weight                              | 2 466 g        |

| General Product Approval                                                          |                                                                                   |                                                                                   |                                                                                   | Declaration of Conformity                                                           | Test Certificates                        |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------|
|  |  |  |  |  | <a href="#">Special Test Certificate</a> |
| CSA                                                                               | UL                                                                                | UR                                                                                |                                                                                   | EG-Konf.                                                                            |                                          |

| Test Certificates             | Shipping Approval                                                                 |                                                                                   | other                         |
|-------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------|
| <a href="#">Miscellaneous</a> |  |  | <a href="#">Miscellaneous</a> |
|                               | PRS                                                                               | RINA                                                                              |                               |

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1213-4AH00>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8US1213-4AH00>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8US1213-4AH00](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1213-4AH00)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

##### Tender specifications

<http://www.siemens.com/specifications>

