





UPC Code: 07847789257

Country Of Origin: Mexico



# WDR20-GY

### **Item Description**

20 Amp, 125 Volt, NEMA 5-20R, 2P, 3W, Decora Plus<sup>™</sup> Duplex Receptacle, Straight Blade, Fed Spec, Heavy Duty Industrial Specification Grade, Weather-Resistant, Self-Grounding, Back & Side Wired, Steel Strap – GRAY

## **Technical Information**

AC Horsepower Rating Horsepower Rating: 1 HP

Electrical Specifications
Amperage: 20 A

Dielectric Voltage: Withstands 3000 V minimum

Grounding: Self-Grounding

**Pole:** 2

Temperature Rise: Max 30 °C after 250 cycles OL at 200 percent rated current

Voltage: 125 VAC Wire: 3

Environmental Specifications Flammability: Rated V-0 per UL 94 Operating Temperature: -40°C to 75°C

Material Specifications

Body Material: PBT Polyester Blend Face Material: PBT Polyester Blend

Ground Clips: Brass

Ground Contacts: 0.030" Brass

Grounding Screw: #8 hex head, triple drive Brass

Line Contacts: 0.030" Phosphor Bronze Mounting Screws: Triple-Drive Plated Steel

Strap Material: Steel Terminal Clamps: Brass Terminal Screws: #8 Triple-Drive Brass

#### Patents\*

CA2483480	US6743029
MX257790	US8684771
MX321216	

\*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

Mechanical Specifications **Product ID:** Ratings are permanently marked on device

Terminal Accom.: #14 AWG - #10 AWG

Terminal ID: Brass - Hot, Green -Ground, Silver - Neutral Termination: Back and Side Wire

Wire Type: Stranded or Solid

Product Features

Color / Feature: Gray Device Type: Decora Plus Duplex Receptacle

Feature: Weather-Resistant Grade: Heavy-Duty Industrial Specification Grade

NEMA: 5-20R

Standards & Certifications

ANSI: C-73

Applicable Standards: UL 498, Fed Spec W-C-596, CSA C22.2. No. 42 Certification/Listing: cULus, NOM-ANCE

NEMA: WD 1 & WD 6 RoHS: RoHS Compliant



## SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

## Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

## Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

## Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

## Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

