


Zinc - Polyolefin Coated

Images



Application

Straight connector for use with metallic and non-metallic "Type B" liquid tight conduit. Suitable for use in Direct Burial applications including concrete encasement, as well as corrosive environments. Nicks or cuts in polyolefin coating can be repaired by heating surface until coating flows. Environmentally safe. UV resistant. Salt spray resistance is greater than 2000 hrs.

Product Information

[Download Photo Image](#) [Download Dimensional Image](#)
Dimension A in Inches: 1.52
Dimension B in Inches: 0.65
Dimension C in Inches: 2.05

Material: Zinc Alloy body with a Polyolefin coating
Finish: Polyolefin Coated

Certifications & Codes:

Federal Specification	A-A-50552
Number:	
NEMA Standard:	FB-1
UL Standard:	UL 514B
UNSPSC:	39121420
ETL File Number:	101498267CRT-001

Catalog ID: 432-LT2C

UPC Number: 78174714432

Description: Connector, Liquid Tight, Direct Burial Rated, Zinc Die Cast, Polyolefin Coated, Size 1 Inch

Application: Straight connector for use with metallic and non-metallic "Type B" liquid tight conduit. Suitable for use in Direct Burial applications including concrete encasement, as well as corrosive environments. Nicks or cuts in polyolefin coating can be repaired by heating surface until coating flows. Environmentally safe. UV resistant. Salt spray resistance is greater than 2000 hrs.

Trade Size: 1"

Std Pkg Qty: 25

Unit Qty: 5