


Zinc - Polyolefin Coated

Images


[Download Photo Image](#)
[Download Dimensional Image](#)

Dimension A in Inches: 2.10

Dimension B in Inches: 0.65

Dimension C in Inches: 3.35

Application

Straight connector for use with metallic and non-metallic "Type B" liquid tight conduit. Suitable for use in Direct Burial applications including concrete encasement, as well as corrosive environments. Nicks or cuts in polyolefin coating can be repaired by heating surface until coating flows. Environmentally safe. UV resistant. Salt spray resistance is greater than 2000 hrs.

Product Information

Material: Zinc Alloy body with a Polyolefin coating

Finish: Polyolefin Coated

Certifications & Codes:

Federal Specification Number:	A-A-50552
NEMA Standard:	FB-1
UL Standard:	UL 514B
UNSPSC:	39121420
ETL File Number:	101498267CRT-001

Catalog ID: 435-LT2C

UPC Number: 78174714435

Description: Connector, Liquid Tight, Direct Burial Rated, Zinc Die Cast, Polyolefin Coated, Size 2 Inch

Application: Straight connector for use with metallic and non-metallic "Type B" liquid tight conduit. Suitable for use in Direct Burial applications including concrete encasement, as well as corrosive environments. Nicks or cuts in polyolefin coating can be repaired by heating surface until coating flows. Environmentally safe. UV resistant. Salt spray resistance is greater than 2000 hrs.

Trade Size: 2"

Std Pkg Qty: 20

Unit Qty: 2