


Steel - Rigid/Liquidtight Transition - Raintight

Images

[Download Photo Image](#)[Download Dimensional Image](#)

Dimension A in Inches: 7/8

Dimension B in Inches: 3/4

Dimension C in Inches: 1-3/16

Application

For a Liquidtight/Raintight Connection between 2 different Raceways. Rigid Conduit IMC and 3/8" Liquidtight Flexible Metallic (LFMC). Suitable for use in wet locations. Concrete Tight

Product Information

Material: Malleable Iron

Finish: Zinc Coated

Certifications & Codes:

CSA File Number: cULus

Federal Specification Number: A-A-50553A

NEMA Standard: FB-1

UL File Number: E9391

UL Standard: 514B

UNSPSC: 39131707

Catalog ID: 4369-LT**UPC Number:** 78174720369

Description: Combination Coupling for transitioning between 3/8" Liquidtight Flexible Metallic Conduit (LFMC) and 1/2" Rigid Steel Conduit. NPSM Threads on Hub. Malleable Iron Body with Steel Ferrule

Application: For a Liquidtight/Raintight Connection between 2 different Raceways. Rigid Conduit IMC and 3/8" Liquidtight Flexible Metallic (LFMC). Suitable for use in wet locations. Concrete Tight

Trade Size: 1/2" - 3/8"**Std Pkg Qty:** 125**Unit Qty:** 25