



Bridgeport Fittings Inc.


705 Lordship Blvd.
Stratford, CT 06615

Phone: 203-377-5944

Fax: 203-381-3488

Malleable

Images



[Download Photo Image](#)

[Download Dimensional Image](#)

Dimension A in Inches: 1.475
Dimension B in Inches: 0.678
Dimension C in Inches: 2.179
Dimension D in Inches: 2.022

Application

45 Degree connector for use with metallic liquid tight conduit. Insulated Throat - 105°C. Liquidtight connectors are suitable for use in Class I, Div 2; Class II, Div 1 and 2; and Class III, Div 1 and 2 hazardous locations.

Product Information

Material: Malleable Iron
Finish: Zinc Electro Plate

Certifications & Codes:

Federal Specification Number: A-A-50552
NEMA Standard: FB-1
UL File Number: E9391, cULus
UL Standard: UL-514B
UNSPSC: 39121420

Catalog ID: 453-SLTI

UPC Number: 78174704453

Description: Connector, Liquid Tight, 45 Degree, Malleable Iron, Insulated Throat - 105°C, Size 1 1/4 Inch

Application: 45 Degree connector for use with metallic liquid tight conduit. Insulated Throat - 105°C. Liquidtight connectors are suitable for use in Class I, Div 2; Class II, Div 1 and 2; and Class III, Div 1 and 2 hazardous locations.

Trade Size: 1-1/4"

Std Pkg Qty: 25

Unit Qty: 5