



**Bridgeport Fittings Inc.**


705 Lordship Blvd.  
Stratford, CT 06615

Phone: 203-377-5944

Fax: 203-381-3488

## Malleable

### Images



[Download Photo Image](#)

[Download Dimensional Image](#)

Dimension A in Inches: 2.343

Dimension B in Inches: 1.136

Dimension C in Inches: 4.484

Dimension D in Inches: 4.232

### Application

45 Degree connector for use with metallic liquid tight conduit. Insulated Throat - 105°C. Liquidtight connectors are suitable for use in Class I, Div 2; Class II, Div 1 and 2; and Class III, Div 1 and 2 hazardous locations.

### Product Information

Material: Malleable Iron

Finish: Zinc Electro-Plate

### Certifications & Codes:

Federal Specification Number: A-A-50552

NEMA Standard: FB-1

UL File Number: E9391, cULus

UL Standard: UL-514B

UNSPSC: 39121420

**Catalog ID:** 457-SLTI

**UPC Number:** 78174704457

**Description:** Connector, Liquid Tight, 45 Degree, Malleable Iron, Insulated Throat - 105 Degree C, Size 3 Inch

**Application:** 45 Degree connector for use with metallic liquid tight conduit. Insulated Throat - 105°C. Liquidtight connectors are suitable for use in Class I, Div 2; Class II, Div 1 and 2; and Class III, Div 1 and 2 hazardous locations.

**Trade Size:** 3"

**Std Pkg Qty:** 1