


## Non-Metallic - Push On - Swivel

### Images



### Application

For Non-Metallic Liquidtight (LNMFC) 0-90 Degree Connector with nylon construction that resists salt water, weak acids, gasoline, alcohol, oil, grease, and many common solvents. No disassembly required, the 480-NMLTS installs by pushing the connector onto the conduit or tubing and tightening the domed sealing nut.

### Product Information

Molded of type 6 nylon. Flammability

Material: classification 94V-2: temperature index 125°C

### Certifications & Codes:

Federal Specification Number: A-A-50552  
NEMA Standard: FB-1  
UL File Number: E9391  
UL Standard: 514B  
UNSPSC: 39121420

[Download Photo Image](#)   [Download Dimensional Image](#)  
Dimension A in Inches: 3.35  
Dimension B in Inches: 2.00  
Dimension C in Inches: .50

**Catalog ID:** 480-NMLTS

**UPC Number:** 78174744480

**Description:** Push-on 1/2" Nylon, Swivel Type, Multi-Angle Connector for 0 to 90 degree Non-Metallic Liquidtight (LNMFC) Connections rubber O-Ring and steel locknut included.

**Application:** For Non-Metallic Liquidtight (LNMFC) 0-90 Degree Connector with nylon construction that resists salt water, weak acids, gasoline, alcohol, oil, grease, and many common solvents. No disassembly required, the 480-NMLTS installs by pushing the connector onto the conduit or tubing and tightening the domed sealing nut.

**Trade Size:** 1/2"

**Std Pkg Qty:** 100

**Unit Qty:** 10