


Non-Metallic - Push On - Swivel

Images

[Download Photo Image](#)[Download Dimensional Image](#)

Dimension A in Inches: 4.00

Dimension B in Inches: 2.40

Dimension C in Inches: .50

Application

For Non-Metallic Liquidtight (LNMFC) 0-90 Degree Connector with nylon construction that resists salt water, weak acids, gasoline, alcohol, oil, grease, and many common solvents. No disassembly required, the 481-NMLTS installs by pushing the connector onto the conduit or tubing and tightening the domed sealing nut.

Product Information

Molded of type 6 nylon. Flammability

Material: classification 94V-2: temperature index 125°C

Certifications & Codes:

Federal Specification Number: A-A-50552

NEMA Standard: FB-1

UL File Number: E9391

UL Standard: 514B

UNSPSC: 39121420

Catalog ID: 481-NMLTS**UPC Number:** 78174744481

Description: Push-on 3/4" Nylon, Swivel Type, Multi-Angle Connector for 0-90 degree Non-Metallic Liquidtight (LNMFC) Connections rubber O-Ring and steel locknut included.

Application: For Non-Metallic Liquidtight (LNMFC) 0-90 Degree Connector with nylon construction that resists salt water, weak acids, gasoline, alcohol, oil, grease, and many common solvents. No disassembly required, the 481-NMLTS installs by pushing the connector onto the conduit or tubing and tightening the domed sealing nut.

Trade Size: 3/4"**Std Pkg Qty:** 100**Unit Qty:** 10