

Bridgeport Fittings Inc.


705 Lordship Blvd. Stratford, CT 06615

Phone: 203-377-5944 Fax: 203-381-3488

Zinc

Images





Download Photo Image Download Dimensional Image

Dimension A in Inches: 1-1/16 Dimension B in Inches: 9/16 Dimension C in Inches: 1-1/2

Application

Straight connector for use with portable cord. Provides liquid tight and watertight protection. Tapered (NPT) threads with gasket and locknut. Supplemental UL listing: Type 4 watertight.

Product Information

Material: Zinc Die Cast

Finish: Ball burnished, mirror smooth

Certifications & Codes:

CSA File Number: LR39354
NEMA Standard: FB-1
UL File Number: E11259
UL Standard: UL-514B
UNSPSC: 39121431

Catalog ID: 771-62

UPC Number: 781747771629

Description: Connector, Cord Grip, Straight, Zinc Die Cast, Size K.O. 3/4 Inch, Cord Range .625 Inch - .750 Inch

Application: Straight connector for use with portable cord. Provides liquid tight and watertight protection. Tapered (NPT) threads with gasket and locknut. Supplemental UL listing: Type 4 watertight.

nothing. Typo Twate

Trade Size: 3/4"

Country of Manufacture: USA

Std Pkg Qty: 50

Unit Qty: 10