



BURNDY Catalog Number
UPC Number
Description
Status

YA312NFXB
 7818100399088
 BELLED HYLUG-263 FLEX-NE
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	5.85
Tongue Type	Standard
Barrell Style	Belled
Bolt Hole Size (in)	0.52
Barrel Type	Long
Thickness	0.18
B Length (in)	2.18
Pad Width (in)	1.29
E - in	1.75
Strip Length	2-1/4

General

Number of Holes	2
Product Description	Copper Compression Lug, 2 Hole w/o Inspection Window, 250 Flex, 1/2" Stud, 1-3/4" Stud Hole Spacing, Long Barrel, Tin Plated

Conductor(s)

Aircraft Cable Size (Range)	N/A
Flex (Class H) Size - Range	250 kcmil
Flex (Class I) Size - Range	250
Copper Solid Size (Range)	N/A
DLO Size (Range)	263 (650/#24)
Navy Cable Size (Range)	N/A
Copper Stranded (Range)	250
Flex (Class G) Size - Range	250 kcmil
Flex (Class M) Size - Range	250

Physical

Type of Plating	Tin
Bolt Hole Size	1/2
Color Code	White
Plated (Yes or No)	Y
Index Number	17
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175