



BURNDY Catalog Number
UPC Number
Description
Status

YAV28L2TC14FX
 7818101030988
 CU HYLUG-4/0FLEX-1/4X5/8
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle
 Length (in)
 Tongue Type
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 E - in
 Strip Length

Straight
 2.86
 Standard
 Chamfered,Skived
 0.27
 Standard
 0.15
 1.03
 1.14
 0.63
 1-1/16

General

Number of Holes

 Product Description

2
 Copper Compression Lug, 2 Hole
 w/ Inspection Window, 4/0 Flex,
 1/4" Stud, 5/8" Stud Hole
 Spacing, Short Barrel, Tin Plated

Conductor(s)

Flex (Class G) Size - Range
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Copper Solid Size (Range)
 DLO Size (Range)
 Copper Stranded (Range)

4/0 AWG
 4/0 AWG
 4/0 AWG
 N/A
 4/0 (550/#24) DLO
 4/0 AWG

Physical

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Tin
 1/4
 Purple
 Y
 15
 Copper

Approvals / Certifications

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS

Y
 Y
 Compliant
 N
 N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175