



BURNDY Catalog Number
UPC Number
Description
Status

YAZ382NTCFX
7818102286788
CULUG-500FLX-LONG W/PORT
Active

Web Use
BURNDY Product Line

Dimensional

Tongue Angle
Strip Length
Length (in)
Barrell Style
Bolt Hole Size (in)
Barrel Type
Thickness
B Length (in)
Pad Width (in)
E - in

Straight
2-3/4
6.72
Skived
0.52
Long
0.27
2.81
1.84
1.75

General

Number of Holes

Product Description

2
Cu Comp Terminal Flex Cond, Bvl
Entry, 2 Hole/W/InspWindow,
535.3 kcmil(1325/#24)DLO, 500
kcmil Flex, 600 V-35 kV, 1/2 "
Stud, 1.75" Spacing, Lng bbl

Conductor(s)

Copper Solid Size (Range)
Navy Cable Size (Range)
Copper Stranded (Range)

N/A
N/A
N/A

Physical

Type of Plating
Bolt Hole Size
Color Code
Plated (Yes or No)
Index Number
Product Material

Tin
1/2
Pink
Y
L99
Copper

Approvals / Certifications

UL Listed
CSA Certified
ROHS Compatible
UL Recognized
CULUS

Y
Y
Compliant
N
N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175