




Industrial Specification Grade Straight Blade Receptacles


2-Pole, 3-Wire Grounding
15A, 125V/AC
20A, 125V/AC
NEMA 5-15R, 5-20R




5734



5362CR



60W47



60W47DPLX

Special Use Panel-Mount Industrial Single Receptacles

Back Wire & Side Wire, Short Strap

15A, 125V
NEMA 5-15R



20A, 125V
NEMA 5-20R



Description	Catalog No. Color Suffix		Catalog No. Color Suffix	
Brown, strap center-center spacing 1.9375" (49.2mm)	☐ 5284 B		☐ 5734 B	

Corrosion Resistant Premium Industrial Grade Receptacles

Back Wire & Side Wire

15A, 125V
NEMA 5-15R



20A, 125V
NEMA 5-20R



Description	Catalog No. Color Suffix		Catalog No. Color Suffix	
Premium Corrosion Resistant Duplex Receptacle	☐ 5262CR GY, Y		☐ 5362CR GY, Y	

Watertight Special Use Industrial Grade Receptacles

Back Wire

15A, 125V
NEMA 5-15R



20A, 125V
NEMA 5-20R



Description	Catalog No. Color		Catalog No. Color	
Single Watertight Receptacle	☐ 60W47 Yellow		☐ 60W33 Yellow	
Single Watertight Receptacle	☐ 60W47BK All-Black		☐ 60W33BK All-Black	
Duplex Watertight Receptacle	☐ 60W47DPLX Yellow		☐ 60W33DPLX Yellow	
Duplex Watertight Receptacle	☐ 60W47DPLXBK All-Black		☐ 60W33DPLXBK All-Black	

Color Ordering Information

For ordering receptacles, include Cat. No. followed by the color code: A (Almond), B (Brown), BK (Black), BL (Blue), GY (Gray), LA (Light Almond), RD (Red), RN (Orange), V (Ivory), W (White), Y (Yellow)

Icon Key



Build-To-Spec Customizable Devices - see page A-4



NAFTA Compliant - see page O-30

Specification Information:

Panel Mount Industrial Receptacles: A-33

Corrosion Resistant Premium Industrial Receptacles: A-37

Watertight Receptacles: A-37