

Commercial Specification Grade Straight Blade Receptacles

2-Pole, 3-Wire Grounding
15A, 125V/AC
NEMA 5-15R



5-15R

Clock Hanger Receptacle

FEATURES

- Single receptacle on recessed wallplate with integral hook.
- High impact- and chemical-resistant nylon face.
- 0.035" (8.73mm) galvanized steel wrap-around yoke mounting strap for superior assembly security.
- Tamper Resistant to comply with 2008 NEC®.

Tamper Resistant NEMA 5-15R, Back Wire & Side Wire



Rating	A	V/AC	Description	Color	Catalog No.	
15	125		Single Clock Hanger Receptacle with Wallplate	W	□ TR775	




Snap-In Receptacles

Large Face NEMA 5-15R




Rating	A	V/AC	Description	Color	Catalog No.	
15	125		Single Receptacle, Plastic Back & Clips, Quick Connect with Screw Terminal Grounding	Black	□ 4067BK	•
			Single Receptacle, Fiber Back & Steel Clips, Quick Connect with Screw Terminal Grounding	Black	□ 4067-01BK	•
			Duplex Receptacle, Plastic Back & Clips, Solder Connect, Slotted Terminals	Black	□ 4070-6BK	•



Rectangular NEMA 5-15R



Rating	A	V/AC	Description	Color	Catalog No.	
15	125		Single Receptacle, Plastic Back & Clips, Quick Connect with Screw Terminal Grounding	Black	□ 67BK	•
			Single Receptacle, Plastic Back & Clips, Quick Connect with Screw Terminal Grounding	White	□ 67W	•
			Single Receptacle, Plastic Back & Clips, Quick Connect with Wire Lead Grounding	Black	□ 67-2BK	•
			Single Receptacle, Plastic Back & Clips, Quick Connect with Wire Lead Grounding	White	□ 67-2W	•
			Plug, Solder Connect, Slotted Terminals	Black	□ 4049BK*	•



* Not NOM

Color Ordering Information

For ordering receptacles, include Cat. No. followed by the color code: A (Almond), B (Brown), BK (Black), BL (Blue), GY (Gray), LA (Light Almond), RD (Red), RN (Orange), V (Ivory), W (White)

Icon Key

- NAFTA Compliant - see page O-30
- Tamper Resistant

Specification Information:

Snap-In Commercial Receptacles: A-36

Commercial Specification Grade Receptacles

2-Pole, 3-Wire Grounding
15A, 125V/AC; 20A, 125V/AC
NEMA 5-15, 5-20

	Device Type	Commercial Grade Duplex and Decorator Duplex Receptacles: BR, CR, 6200, 6300, 6400 Series	Commercial Grade Single Receptacles: 800, 1800 Series	Snap-In Receptacles: 49, 67, 4049, 4067, 4070 Series
	Wiring Type	Back & side wire, except CR, 6250, 6350, 6450 series	Side wire	Wire leads & quick connect
	Testing & Code Compliance	<ul style="list-style-type: none"> cULus Listed to UL 498, file no. E15058 	<ul style="list-style-type: none"> Listed to UL 498, file no. E15058 	<ul style="list-style-type: none"> UR (UL Recognized)
		<ul style="list-style-type: none"> BR series only: UL verified to Federal Spec. WC-596G 	<ul style="list-style-type: none"> CSA certified to 22.2, no 42, file no. 6914 (6233-01) 	<ul style="list-style-type: none"> CSA certified to C22.2, no. 42, file no. 6914 (6233-01)
		<ul style="list-style-type: none"> CSA certified to 22.2, no 42, file no. 6914 (6233-01) 	<ul style="list-style-type: none"> NOM/ANSI certified 	<ul style="list-style-type: none"> NOM certified
		<ul style="list-style-type: none"> NOM/ANSI certified 		
Specifications: Environmental	Flammability	Meets UL 94 requirements; V2 rated	Meets UL 94 requirements; V2 rated	Meets UL 94 requirements; V2 rated
	Temperature Rating	-20°C to 70°C (-4°F to 158°F)	-20°C to 70°C (-4°F to 158°F)	-20°C to 70°C (-4°F to 158°F)
Specifications: Electrical	Dielectric Voltage	Withstands 2000V per UL 498	Withstands 2000V per UL 498	Withstands 2000V per UL 498
	Current Interrupting	Yes, at full-rated current	Yes, at full-rated current	Yes, at full-rated current
	Temperature Rise	Max. 30°C (86°F) after 250 cycles of overload @ 200% of rated current (DC)	Max. 30°C (86°F) after 100 cycles of overload @ 150% of rated current (DC)	Max. 30°C (86°F) after 100 cycles of overload @ 150% of rated current (DC)
Specifications: Mechanical	Terminal Accommodation	#14 - 10 AWG	#14 - 10 AWG	#14 - 12 AWG
	Voltage Ratings	Permanently marked on device	Permanently marked on device	Permanently marked on device
Materials:	Face	Nylon	Nylon	Urea
	Base	PVC	Nylon	Polypropylene
	Strap	0.045" thick galvanized steel	0.040" thick galvanized steel	0.030" thick steel
	Auto Ground Clip	Phosphor bronze	0.032" brass	N/A
	Line Contacts	0.030" thick brass	0.030" thick brass	0.032" thick brass
	Ground Contact	Riveted	Riveted	Screw down
	Terminal Screws	Terminal: #8-32 brass, neutral screw nickel plated	Terminal: #8-32 brass, neutral screw nickel plated	N/A
	Ground Screw	Ground: #8-32 brass (green)	Ground: #8-32 brass (green)	Ground: #6-32 brass (green)