




Hospital Specification Grade Straight Blade Receptacles

2-Pole, 3-Wire Grounding
 15A, 250V/AC
 20A, 250V/AC
 NEMA 6-15R, 6-20R



Premium Hospital Grade Receptacles

Back Wire & Side Wire	15A, 250V NEMA 6-15R	UL FULS SP	20A, 250V NEMA 6-20R	UL FULS SP
Description	Catalog No. Color Suffix	▶	Catalog No. Color Suffix	▶
● Premium Duplex Receptacle	<input type="checkbox"/> AH8600 ____ V, W	•	<input type="checkbox"/> AH8400 ____ B, GY, RD, V, W	•
● Premium Single Receptacle	<input type="checkbox"/> 8610 ____ V, W	•	<input type="checkbox"/> 8410 ____ B, GY, RD, V, W	•



Isolated Ground Premium Hospital Grade Receptacles

Back Wire & Side Wire	20A, 250V NEMA 6-20R	UL FULS SP
Description	Catalog No. Color Suffix	
● Premium IG Duplex Receptacle	<input type="checkbox"/> IG8400 ____ RN	•

Color Ordering Information

For ordering receptacles, include Cat. No. followed by the color code: A (Almond), B (Brown), BK (Black), BL (Blue), GY (Gray), LA (Light Almond), RD (Red), RN (Orange), V (Ivory), W (White)

Icon Key

▶ ArrowLink™ option available. Add "M" suffix to Standard catalog number (example AH8600W, AH8600WM). For ordering information on ArrowLink & ArrowLink SPD connectors, see page A-3.

Build-To-Spec Customizable Devices - see page A-4
 NAFTA Compliant - see page O-30

● Hospital Grade

Accessories for Hospital Grade NEMA 6-15 & 6-20 Receptacles

Description	Catalog No.	
1-Gang standard size duplex receptacle nylon wallplate, ivory	<input type="checkbox"/> 5132V	•
1-Gang standard size single receptacle, stainless steel wallplate, REPEL	<input type="checkbox"/> 93091AM	•
1-Gang mid-size duplex receptacle polycarbonate wallplate, light almond	<input type="checkbox"/> PJ8LA	
1-Gang standard size duplex receptacle stainless steel wallplate, REPEL	<input type="checkbox"/> 93101AM	•

Specification Information:

Premium HG Receptacles: A-24

ArrowLink Premium HG Receptacles: A-28 & A-29

Isolated Ground HG Receptacles: A-25



5132V



93091AM



PJ8



93101AM

Hospital Specification Grade Premium Receptacles

2-Pole, 3-Wire Grounding
15A, 125V/AC; 15A, 250V/AC; 20A, 125V/AC; 20A 250V/AC
NEMA 5-15, 6-15, 5-20, 6-20

	Device Type	Hospital Grade Premium Duplex Receptacles: AH8200, AH8300, AH8400, AH8600 Series	Hospital Grade Premium Decorator Duplex Receptacles: 8262, 8362 Series	Hospital Grade Premium Single Receptacles: 8210, 8310, 8410, 8610 Series
	Wiring Type	Back & side wire	Back & side wire	Back & side wire
	Testing & Code Compliance	<ul style="list-style-type: none"> Listed to UL 498, file no. E15058 	<ul style="list-style-type: none"> Listed to UL 498, file no. E15058 	<ul style="list-style-type: none"> Listed to UL 498, file no. E15058
		<ul style="list-style-type: none"> UL verified to Federal Spec. WC-596G 	<ul style="list-style-type: none"> UL verified to Federal Spec. WC-596G 	<ul style="list-style-type: none"> UL verified to Federal Spec. WC-596G
		<ul style="list-style-type: none"> CSA certified to C22.2, no. 42, file no. 6914 (6233-01) 	<ul style="list-style-type: none"> CSA certified to C22.2, no. 42, file no. 6914 (6233-01) 	<ul style="list-style-type: none"> CSA certified to C22.2, no. 42, file no. 6914 (6233-01)
		<ul style="list-style-type: none"> NOM certified 	<ul style="list-style-type: none"> NOM certified 	<ul style="list-style-type: none"> NOM certified
Specifications: Environmental	Flammability	Meets UL 94 requirements; V2 rated	Meets UL 94 requirements; V2 rated	Meets UL 94 requirements; V2 rated
	Temperature Rating	-20°C to 90°C (-4°F to 194°F)	-20°C to 70°C (-4°F to 158°F)	-20°C to 90°C (-4°F to 194°F)
Specifications: Electrical	Dielectric Voltage	Withstands 2000V per UL 498	Withstands 2000V per UL 498	Withstands 2000V per UL 498
	Current Interrupting	Yes, at full-rated current	Yes, at full-rated current	Yes, at full-rated current
	Temperature Rise	Max. 30°C (86°F) after 250 cycles of overload @ 200% of rated current (DC)	Max. 30°C (86°F) after 250 cycles of overload @ 200% of rated current (DC)	Max. 30°C (86°F) after 250 cycles of overload @ 200% of rated current (DC)
Specifications: Mechanical	Terminal Accommodation	#14 - 10 AWG	#14 - 10 AWG	#14 - 10 AWG
	Voltage Ratings	Permanently marked on device	Permanently marked on device	Permanently marked on device
Materials:	Face	Nylon	Nylon	Nylon
	Base	Glass-filled nylon	Glass-filled nylon	Nylon
	Strap	0.05" thick brass, nickel plated	0.05" thick brass	0.05" thick galvanized steel
	Auto Ground Clip	Brass	Brass	Phosphor bronze
	Line Contacts	0.031" thick 5-leaf brass, nickel plated	5-leaf brass	0.031" thick triple-wipe brass
	Ground Contact	Integral	Integral	Riveted
	Terminal Screws	#8-32 brass, neutral screw nickel plated	#8-32 steel	#8-32 steel, brass plated, neutral screw nickel plated
	Ground Screw	#8-32 brass (green)	#8-32 steel (green)	#8-32 steel, brass plated (green)
	Screw Terminal Guards	PVC hinged doors	PVC hinged doors	N/A
	Illuminated Models	Long-life neon bulb	Long-life neon bulb	N/A