

## Commercial Specification Grade AC Specialty Switches

1A, 125V/AC; 1A, 250V/AC  
 3A, 125V/AC; 3A, 250V/AC  
 6A, 125V/AC  
 Single-Pole, Two-Circuit



449NP

### Canopy Switches

#### FEATURES

- Wide variety of sizes for use in fixtures, appliances, doorways and equipment.
- Shank is threaded 15/32"-32 x 15/32" (11.8mm) long.
- Hex nut and finishing nut furnished.
- 6" (152.4mm) wire lead terminals, #18 105°C stripped 0.75" (19.1mm).

#### Push Button



Rating A V/AC	Circuit	Description	Sequence	Finish	Catalog No.
1A 125V "T" 1A 250V 3A 250V	Single-Pole	Metal Push Button	On-Off	Nickel	☐ 449NP



458BD

#### Pull Chain



Rating A V/AC	Circuit	Description	Sequence	Finish	Catalog No.
1A 125V "T" 1A 250V 3A 125V	Single-Pole	Pull Chain with End Bell	On-Off	Nickel	☐ 458NP
1A 125V "T" 1A 250V 3A 125V	Single-Pole	Pull Chain with End Bell	On-Off	Brass	☐ 458BD
3A 125V "T" 3A 250V 6A 125V	Single-Pole	Pull Chain with End Bell	On-Off	Nickel	☐ 442




442

#### Pull Chain



Rating A V/AC	Circuit	Description	Sequence	Finish	Catalog No.
3A 250V 6A 125V	Two-Circuit	Pull Chain with End Bell	Lo-Med-Hi-Off	Brass	☐ 460



460

### Circuit Control Toggle Switch

#### FEATURES

- Shank is threaded 15/32"-32 x 9/32" (7.1mm) long.
- Keyed shank, indicator plate and finishing nut furnished.
- 6" (152.4mm) wire leads, #18 105°C stripped 0.75" (19.1mm).

#### Bat Handle



Rating A V/AC	Circuit	Description	Sequence	Catalog No.
3A 250V 6A 125V	SPST	Metal Bat Handle	On-Off	☐ 452



452

#### Icon Key

NAFTA Compliant - see page O-30

## Canopy Switches

Single-Pole, Two-Circuit

1A, 125V/AC; 1A, 250V/AC

3A, 125V/AC; 3A, 250V/AC; 6A, 125V/AC; 6A, 250V/AC

### FEATURES

- Wide variety of sizes for use in fixtures, appliances, doorways and with equipment.
- Shank is threaded 15/32"-32 x 15/32" (11.8mm) long.
- Hex nut and finishing nut furnished.
- 6" (152.4mm) wire lead terminals, #18 105°C stripped 0.75" (19.1mm).



### Push Button Canopy Switches

1A 125V/AC "T", 1A 250V/AC, 3A 250V/AC

Description	Color	Catalog No.
Metal Push Button, Single-Pole, On-Off Sequence	Nickel	□ 449NP

449NP



UL Recognized component for US & Canada, file no. E81103

## Circuit Control Switches

Single-Pole, Single Throw

1A, 125V/AC; 1A, 250V/AC; 3A, 125V/AC

### FEATURES

- Shank is threaded 15/32"-32 x 15/32" (11.8mm) long.
- Keyed shank, indicator plate and finishing nut furnished.
- 6" (152.4mm) wire lead terminals, #18 AWG 105°C stripped 0.75" (19.1mm).



### Circuit Control Toggle Switch

1A 125V/AC "T", 1A 250V/AC, 3A 125V/AC

Description	Color	Catalog No.
Metal Bat Handle, Single-Pole Single Throw Circuit, On-Off Sequence	Silver	□ 452

452



UL Recognized component for US & Canada, file no. E18704; CSA certified

Dimensional Information: B-60

Specification Information: Please visit  
[www.cooperwiringdevices.com](http://www.cooperwiringdevices.com)