

Service Entrance Heads

For Rigid Conduit, EMT & IMC

Type CT - Clamp Type

Combination Entrance Caps

Use:

Provides a weather-resistant termination of a Service Entrance Conduit Riser at utility connection point.

Features:

- Bar type pressure clamp in body.
- Screw does not bear directly on conduit.
- Weather resistant.
- Phenolic Insulator has predrilled holes to slip over conductors.
- Easy to assemble onto conduit riser.

Material:

Malleable iron
Brass screws in hood
Phenolic insulator

Finish:

Hot Dip or Mechanically Galvanized



Third Party Certification:




Applicable Third Party Standards:

UL Standard: 514B

Trade Size (inches)	Catalog Number	Insulator Hole No. Holes	Insulator Hole Size (inches)	Dimensions in Inches		
				A	B	C
1/2	CT-50G	4	9/16	2 3/8	2 1/16	2 7/8
3/4	CT-75G	2 3	3/8 13/32	3 3/16	2 5/16	3 1/8
1	CT-100G	2 3	7/16 1/2	3 3/4	2 11/16	3 1/2
1 1/4	CT-125G	2 3	27/64 5/8	4 1/2	3 3/16	3 13/16
1 1/2	CT-150G	3 2 1	3/4 19/32 7/16	5 5/8	3 25/32	4 3/4
2	CT-200G	2 3 1	3/4 1 17/32	7	4 3/4	6 5/16



Type CT-50G



Type CT-100G

Type CT-2

Slip Fitter Mast Cap

Use:

Combination entrance cap to fit 2" mast and has 1 1/4" cap.

Features:

- Bar type pressure clamp in body.
- Screw does not bear directly on conduit.
- Weather resistant.
- Phenolic Insulator has predrilled holes to slip over conductors.
- Easy to assemble onto conduit riser.



Material:

Malleable iron
Phenolic insulator

Finish:


Hot Dip or Mechanically Galvanized

Trade Size (inches)	Catalog Number	Insulator Hole No. Holes	Insulator Hole Size (inches)	Dimension in Inches		
				A	B	C
2-1 1/4	CT-2-125G	2 3	27/64 5/8	5	3 3/16	5 1/16



Type CT-2

Third Party Certification:



Applicable Third Party Standards:

UL Standard: 514B