

Service Entrance Heads

Threaded For Rigid Conduit or IMC

Type 17

Entrance Caps

Use:

Provides a weather-resistant termination of a Service Entrance Conduit Riser at utility connection point.

Features:

- Weather resistant.
- Phenolic Insulator has predrilled holes to slip over conductors.
- Easy to assemble onto conduit riser.

Material:

Malleable or Ductile Iron
Phenolic Insulator

Finish:

Hot Dip or Mechanically Galvanized

Third Party Certification:



UL Listed: E-11857




CSA Certified: 9795

Applicable Third Party Standards:


UL Standard: 514B
CSA Standard C22.2 No. 18

Trade Size (inches)	Catalog Number	Insulator No. Holes	Hole Dia. (inches)	Dimensions in Inches		
				A	B	C
½	17-50G	4	1⁹⁄₆₄	3⅞	2⅞₁₆	2⅞
¾	17-75G	2 3	⅜ 1⅜₃₂	3⅞₁₆	2⅞₁₆	2⅞₁₆
1	17-100G	2 3	⅞₁₆ ½	3¾	2¹¹⁄₁₆	2¹³⁄₁₆
1¼	17-125G	2 3	27⁄₆₄ ¾	4⅞₁₆	3⅞	3¾
1½	17-150G	3 1	⅞ ⅞₁₆	5	3⅞₁₆	3⅞₁₆
2	17-200G	2 3 1	¾ 1 1⅜₃₂	5	5¾	6¹⁵⁄₁₆
2½	17-250G	3 1 3	⅞ 1 1⅞₁₆	10⁹⁄₁₆	6⅞	6⅞₁₆
3	17-300G	4 2	1¾ 1⅞	12⁹⁄₁₆	8	8⅞₁₆
3½	17-350G	4 2	1¾ 1⅞	12⁹⁄₁₆	8	8¾
4	17-400G	4 2	1¾ 1⅞	12½	8	8⅞₁₆
5	17-500G	*	*	12¾	13⅞₁₆	10½
6	17-600G	*	*	17¾	15⅞	12½

*Holes Furnished as Specified. No Charge.



Type 17-50G thru 17-400G



Type 17-500G & 17-600G

