



Features

- Wattage selectable at time of installation.
- Models shipped wired to highest wattage.
- Approved for horizontal mounting - right or left discharge.
- Fan purge circuit.
- Disconnect switch.
- Drywall depth embossments on back can.
- 18 gauge powder coated steel & extruded Aluminum front.
- Manual reset thermal limit.
- Steel block fin element.
- Propeller style fan blade: 1060 RPM motor; 100 CFM.
- Weight 6 lbs.
- Rough in dimensions: 9 1/4" Wide x 12 1/8" High x 3 5/8" Deep.
- Grill dimensions: 10" Wide x 13 1/8" High.
- Approved for wall or ceiling installation.
- Made in U.S.A.

Standard Models

| MFG CATALOG NUMBER | MFG MODEL NUMBER | SELECTABLE INSTALLATION WATTAGE | MAX BTU _s | VOLTS | MAX AMPS |
|---|------------------|---|----------------------|-----------|----------|
| TAMPERPROOF IN-BUILT DOUBLE POLE THERMOSTAT (40° - 100° TEMPERATURE RANGE) | | | | | |
| 09962102 | E3055T2DWB | 750 or 1500 | 5120 | 120 | 12.5 |
| 09962202 | E3058T2DWB | 900 or 1800 | 6143 | 120 | 15.0 |
| 09962502 | F3052T2DWB | 1000 or 2000 | 6826 | 208 | 8.3 |
| 09456902 | F30522T2DWB | 500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250 | 7680 | 208 | 10.8 |
| 09962802 | H3052T2DWB | 750 or 1000 - 1500 or 2000 | 6826 | 208 / 240 | 8.3 |
| 09457202 | H30522T2DWB | 500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250 | 7680 | 240 | 9.4 |
| 09963102 | G3052T2DWB | 2000 | 6826 | 277 | 7.2 |
| TAMPERPROOF IN-BUILT SINGLE POLE THERMOSTAT (0° - 110° TEMPERATURE RANGE) | | | | | |
| 09960602 | E3055TDWB | 750 or 1500 | 5120 | 120 | 12.5 |
| 09960702 | E3058TDWB | 900 or 1800 | 6143 | 120 | 15.0 |
| 09961002 | F3052TDWB | 1000 or 2000 | 6826 | 208 | 8.3 |
| 09456302 | F30522TDWB | 500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250 | 7680 | 208 | 10.8 |
| 09961302 | H3052TDWB | 750 or 1000 - 1500 or 2000 | 6826 | 208 / 240 | 8.3 |
| 09456602 | H30522TDWB | 500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250 | 7680 | 240 | 9.4 |
| 09961602 | G3052TDWB | 2000 | 6826 | 277 | 7.2 |

Accessories

| MFG CATALOG NUMBER | MFG MODEL NUMBER | DESCRIPTION |
|--------------------|------------------|------------------------|
| 09969402 | 305EX8 | 1" EXTENDER |
| 09969302 | 305EX16 | 2" EXTENDER |
| 09969202 | 305EX32 | 4" SURFACE MOUNT FRAME |