

5100 Series Horizontal or Vertical Mounted Fan Forced Unit Heater

16

Standard Taskmaster Models & Series Notes

MFG CATALOG NUMBER	MFG MODEL NUMBER	KW	BTUs / H	VOLTS	PH	AMPS	CONTROL VOLTAGE	TEMP RISE	AIR THROW	CFM	RECOMMENDED MOUNTING HT.		WT. (LBS)
											Horizontal	Vertical	
06450802	F1F5103N	3.3	11.2	208	1	15.9 / 9.17	208	26°F	12'	400	9'	9'	25
06451002	HF1B5103N	3.3/2.5	11.2 / 8.5	240/208	1	13.7 / 11.9	240 / 208						
06456802	F2F5103N	3.3	11.2	208	1 / 3	15.9 / 9.17	208						
06457002	HF2B5103N	3.3/2.5	11.2 / 8.5	240/208	1 / 3 3	13.7 / 11.9 7.9 / 6.9	240 / 208						
06457202	G1G5103N	3.3	11.2	277	1	11.9	277						
06451202	P3P5103CA1N			480	3	4.0	24						
06455402	F1F5105N	5.0	17.1	208	1	24.1	208	40°F	12'	400	9'	9'	25
06455602	HF1B5105N	5.0/3.7	17.1 / 12.8	240/208	1	20.9 / 18.1	240 / 208						
06451402	F2F5105N	5.0	17.1	208	1 / 3 3	24.1 13.9	208						
06451602	HF2B5105N	5.0 3.7	17.1 12.8	240 208	1 / 3 1 / 3	20.8 / 18.1 12.1 / 10.4	240 208						
06458402	G1G5105N	5.0	17.1	277	1	18.1	277						27
06451802	P3P5105CA1N	5.0	17.1	480	3	6.1	24						
06452002	F2F5107CA1L	7.5	25.6	208	1 / 3	36.1 / 20.8	24						
06452202	HF2B5107CA1L	7.5 5.6	25.6 19.2	240 208	1 / 3 1 / 3	27.1 / 31.3 31.3 / 27.1							
06459202	G1G5107CA1L	7.5	25.6	277	1	27.1							
06452402	P3P5107CA1N	7.5	25.6	480	3	9.1							
06452602	F2F5110CA1L	9.9 10.0	33.8 34.1	208 240	1 / 3 1 / 3	47.8 / 27.4 41.2 / 24.0							
06452802	HF2B5110CA1L	7.5	25.6	208	1 / 3	36.1 / 20.8							
06456402	G1G5110CA1N	10.0	34.1	277	1	36.1							
06453002	P3P5110CA1N	10.0	34.1	480	3	12.1							
06453202	F3F5115CA1L	15.0	51.2	208	3	41.7							
06453402	HF3B5115CA1L	15.0/11.2	51.2 / 38.4	240/208	3	36.1 / 31.3							
06453602	P3P5115CA1N	15.0	51.2	480	3	18.1							
06453802	HF3B5120CA1L	19.7/14.8	67.2 / 50.5	240/208	3	47.8 / 41.1							
06454002	P3P5120CA1N	20.0	68.3	480	3	24.1							
06458802	F3F5125CA1L	25.0	85.3	208	3	69.5							
06459402	HF3B5125CA1L	25.0/18.7	85.3 / 64.0	240/208	3	60.2 / 52.1							
06459802	P3P5125CA1N	25.0	85.3	480	3	30.1							
06454202	F3F5130CA1L	30.0	102.4	208	3	83.4							
06454402	HF3B5130CA1L	30.0/22.5	102.4 / 76.8	240/208	3	72.3 / 62.5							
06454602	P3P5130CA1N	30.0	102.4	480	3	36.2							
06440402	F3F5140CA1L	40.0	136.5	208	3	111.2							
06440602	HF3B5140CA1L	40.0/30.0	136.5/102.4	240/208	3	96.4 / 83.4							
06440802	P3P5140CA1N	39.0	133.1	480	3	47.0							
06454802	F3F5150CA1L	49.6	169.3	208	3	139.0							
06455002	HF3B5150CA1L	50.0/37.5	170.6/128.0	240/208	3	120.5/104.3							
06455202	P3P5150CA1N	50.0	170.6	480	3	60.3							
									51/56°F	50'	3100/2800	15'	22'

International Models

MFG CATALOG NUMBER	MFG MODEL NUMBER	KW	BTUs / H	VOLTS	PH	AMPS	CONTROL VOLTAGE	TEMP RISE	AIR THROW	CFM	RECOMMENDED MOUNTING HT.		WT. (LBS)					
											Horizontal	Vertical						
07153002	Q3H5103CA1	3.3	11263	380	3	5.02	24	26	12'	400	9'	9'	25					
07249202	R3H5103CA1			415		4.6												
07249302	Q3H5105CA1			380		7.6												
04249402	R3H5105CA1	5.0	17065	415		6.96		40					22'	700	10'	12'	54	
07171302	Q3H5107CA1			380		11.4												
07249502	R3H5107CA1			415		10.5												
06865702	Q3H5110CA1	7.5	25600	380		15.2		34	45	10'	14'	55						
07249602	R3H5110CA1			415		13.9												
07249702	Q3H5115CA1			380		22.8												
07249802	R3H5115CA1	15.0	51195	415		20.9		43	32'	1100	11'	20'						64
07041702	Q3H5120CA1			380		30.4												
07249902	R3H5120CA1			415		27.85												
07191902	Q3H5125CA1	25.0	85325	380		38.0		40/44	45'	2000/1800	12'	22'	120					
07106102	R3H5125CA1			415		34.8												
07250002	Q3H5130CA1			380		45.6												
07106202	R3H5130CA1	30.0	102390	415		41.8		47/53	40'	3100/2800	15'	24'						
07250102	Q3H5140CA1			380		60.85												
07098302	R3H5140CA1			415		55.7												

• For 24V control add "CA1" suffix. • For 120V control add "CA2" suffix. • For other voltages consult factory.

NOTES:

- 25-50KW models are wired for single or two stage heating and have two speed motors.
- Air delivery and motor data on dual voltage units reflect higher voltage.
- 600 Volt models available in 5 KW through 30 KW. Contact factory for delivery.
- Supply wire on 40 and 50 KW models should have rated insulation of 75°C minimum.
- Use T5122 for two stage control.
- Use TW123 for two stage control.
- Use TFS5102 for two stage control.
- Wall thermostat must be used when built-in stratification thermostat is required.

5100 Series Horizontal or Vertical Mounted Fan Forced Unit Heater

Recommended Control Options, Control Accessory Options, & Control Accessories

17

MFG MODEL NUMBER	DISCONNECT SWITCH		THERMOSTAT		SUMMER FAN SWITCH		THERMOSTAT & SUMMER FAN SWITCH WALL MOUNTED	STRATIFICATION THERMOSTAT						
	1 Ø	3 Ø	IN-BUILT	WALL MOUNTED	IN-BUILT	WALL MOUNTED		IN-BUILT	WALL MOUNTED					
F1F5103N	DCS 202	NA	T5100	ET5SS	FS5101	FSW5111	NA	TC5103	TC1602					
HF1B5103N														
F2F5103N														
HF2B5103N	DCS 202	NA	T5100	ET 5SS	FS5102	FSW5112	TFS5101	TC5102	NA					
	NA	DCS 403	T5102	TW 1512										
G1G5103N	DCS 202	NA	T5100	ET5SS										
P3P5103CA1N	NA	DCS 403		RK120EAA										
F1F5105N	DCS 403	NA		S2025	FS5101	FSW5111	NA	TC5103	TC1602					
HF1B5105N			ET5SS											
F2F5105N			S2025											
HF2B5105N	NA	DCS 403	T5102	TW 1512	FS5102	FSW5112	TFS5101	TC5103	TC1602					
	DCS 403	NA	T5100	ET5SS										
	NA	DCS 403	T5102	TW 1512										
G1G5105N	DCS 403	NA	T5100	S2025	FS5101	FSW5111	TFS5101	TC5103	TC1602					
P3P5105CA1N	NA	DCS 403		RK120EAA						FS5102	FSW5112	TC5102	NA	
F2F5107CA1L	DCS 403	NA												
	NA	DCS 403			FS5101	FSW5111	TC5103	TC1602						
HF2B5107CA1L	DCS 403	NA												
	NA	DCS 403							FS5102	FSW5112	TC5102	NA		
G1G5107CA1L	DCS 403	NA												
P3P5107CA1L	NA	DCS 403			FS5101	FSW5111	TC5103	TC1602						
F2F5110CA1L	DCS 603	NA												
	NA	DCS 403							FS5102	FSW5112	TC5102	NA		
HF2B5110CA1L	DCS 603	NA												
	NA	DCS 403			FS5101	FSW5111	TC5103	TC1602						
G1G5110CA1N	DCS 603	NA												
P3P5110CA1N	NA	DCS 403	T5100						TW123	FS5101	FSW5111	TFS5101	TC5103	TC1602
F3F5115CA1L		DCS 603			FS5102	FSW5112	TC5102	NA						
HF3B5115CA1L		DCS 603												
P3P5115CA1L		DCS 603								FS5102	FSW5112	TC5102	NA	
HF3B5120CA1L		DCS 603			FS5101	FSW5111	TC5103	TC1602						
P3P5120CA1N		DCS 403												FS5102
F3F5125CA1L		DCS 1003		FS5101						FSW5111	TC5103	TC1602		
HF3B5125CA1L		DCS 403			FS5102	FSW5112	TC5102	NA						
P3P5125CA1N		NA											FS5101	FSW5111
F3F5130CA1L		DCS 1003		FS5102						FSW5112	TC5102	NA		
HF3B5130CA1L		DCS 603			FS5101	FSW5111	TC5103	TC1602						
P3P5130CA1N		DCS 603											FS5102	FSW5112
F3F5140CA1L		NA		FS5101						FSW5111	TC5103	TC1602		
HF3B5140CA1L		NA			FS5102	FSW5112	TC5102	NA						
P3P5140CA1N		DCS 603											FS5101	FSW5111
F3F5150CA1L		NA		FS5102						FSW5112	TC5102	NA		
HF3B5150CA1L		DCS 1003			FS5101	FSW5111	TC5103	TC1602						
P3P5150CA1N		DCS 1003											FS5102	FSW5112

CONTROL ACCESSORY OPTIONS - FIELD INSTALLED IN HEATER		
MFG CATALOG NUMBER	MFG MODEL NUMBER	DESCRIPTION
POWER DISCONNECT SWITCH*		
07171502	DCS202 / 5100	20 AMP; 0-16 Amps
07171602	DCS403 / 5100	40 AMP; 16.1-32 Amps
07171702	DCS603 / 5100	60 AMP; 32.1-48 Amps
07171802	DCS1003 / 5100	100 AMP; 48.1-80 Amps
*Disconnect must be rated at 80% of total ampload.		
LINE VOLTAGE THERMOSTAT		
06927702	T5100	SPST; LINE DUTY 25 AMP, 120-277V, (40-100 °F)
06927802	T5102	DPST; LINE DUTY 25 AMP 120-277V 25 AMP, 120-277V, (60-120 °F)
LOW VOLTAGE THERMOSTAT (ALL CA1 MODELS) (45 - 90 °F)		
06927702	T5100	SPST; LOW VOLT/PILOT DUTY; 125VA; (3.3-20 KW UNITS)
06927902	T5122	2-STAGE; LOW VOLT; 125VA; (25-50 KW UNITS)
STRATIFICATION THERMOSTAT		
06928002	TC5102	SPST; LOW VOLT/PILOT DUTY (W/RELAY) ; 70-130°
06928102	TC5103	SPST; LINE DUTY; AMP 120-240V; 70-130°
SUMMER FAN SWITCH		
06928202	FS5101	SPST; LINE VOLT ;120-277V
06928302	FS5102	SPST; LINE VOLT ; 480-600V

CONTROL ACCESSORIES - REMOTE WALL MOUNTED		
MFG CATALOG NUMBER	MFG MODEL NUMBER	DESCRIPTION
LINE VOLTAGE THERMOSTAT		
05029102	S2025H10AA**	SP; 25 Amp; 120-277V; 50-90°F
05387802	ET5SS**	SP; 22 Amp; 120-277V; 50-90°F
06910902	TW1512*	DPST; 25 AMP; 120-277V; 50-90°F
LOW VOLTAGE THERMOSTAT (ALL CA1 MODELS)		
02600002	RK120EAA	24VAC or MV; 50°-90°F
06911102	TW123	2-STAGE; (25 - 50 KW UNITS); 40-90°F
STRATIFICATION THERMOSTAT		
06911002	TC1602	SPST; LINE VOLT; 120-277V; 70-140°
SUMMER FAN SWITCH		
06926202	FSW5111	SPST; LINE VOLT; 120-277V
06926302	FSW5112	SPST; LOW VOLT; (W/RELAY)
LOW VOLTAGE THERMOSTAT & SUMMER FAN SWITCH(W/RELAY) (CA1 MODELS)		
06926402	TFS5101	SPST; LOW VOLT; 50-90°
06926502	TFS5102	2-STAGE; LOW VOLT; 50-90°

**Any SPST thermostat of sufficient amperage may be substituted.
*Use DPST double line break thermostat for 3-phase line voltage control in non "C" models.