

# Portable 18" Self Contained Power Mister



**SELF CONTAINED MISTING SYSTEM WITH WATER PUMPED FROM A 10 GALLON TANK OR VESSEL.**

### Features

- Toggle Switch - fan only or fan & mist
- SJT type cord - 3 conductor - 18' long with GFCI plug
- 18" Aluminum blade
- Spiral front and rear wire guards
- Standard model - Low Pressure 85 PSI diaphragm pump
- HD model - Medium Pressure 125 PSI diaphragm pump
- Meets OSHA standards / 1 year limited warranty / Made in U.S.A.

### Motor Specification

- 1-Speed, 1/8 HP
- Sleeve bearing
- Permanently lubricated
- 1-Phase, 120 Volt
- Totally enclosed
- Permanent split capacitor

Note: Tank lid not included.

### Standard Models

MFG CATALOG NUMBER	MFG MODEL NUMBER	FAN SIZE	TYPE	MOTOR HP	CFM*	AMPS	WT. (LBS)	VELOCITY PROFILE	
								CFM / Area Sq Ft	
08554702	PM-18S	18"	HAND CARRY	1/10	1900	1.1	30	3100 / 140	
08775702	PM-18S-HD								
08554702	PM-18C	18"	CART	1/10	1900	1.1	30		
08775602	PM-18C-HD								
08760702	NK-PM18	---	REPLACEMENT NOZZLE KIT					---	

\*Measured 2 feet from face of fan

18" Fan & Pump Lid for 10gal. Tank

MFG CATALOG NUMBER	MFG MODEL NUMBER	WT. (LBS)
08555202	PM-18FO	28
08775802	PM-18FO-HD	28

## Industrial Ceiling Fans



### Features

- All metal construction, white epoxy finish
- 24" down rod with safety cable
- Mounts to 3/8" diameter steel J-hook
- 18 pole (motor), 115V, 1-Phase, capacitor type, impedance protected motor with sealed ball bearings
- Imported to TPI specifications

Note: Photograph is a representation of stocked models. Actual model may vary in appearance.

### Commercial Grade

- Assembly required
- 30" lead wires
- 1 year limited warranty

### Industrial Grade

- Fully assembled except blade bolt down
- 3 conductor cord, 30" long with plug
- Permanently lubricated
- 3 year limited warranty

### Heavy Duty Grade

- Fully assembled except blade bolt down
- 3 conductor cord, 30" long with plug
- Permanently lubricated
- 6 year limited warranty

### Standard Models

GRADE	MFG CATALOG NUMBER	MFG MODEL NUMBER	TYPE	SIZE	VOLTS	CFM	RPM	AMPS	WT. (LBS)
Commercial	08529602	CHR-56*	Down Draft	56"	120	7000	320	0.6	15
Industrial	07979902	IHR-48	Down Draft	48"	120	5000	320	0.53	14
Industrial	07971502	IHR-56	Down Draft	56"	120	7000	310	0.6	15
Industrial	07980002	IHR-56R*	Reversible	56"	120	7000	310	0.55	14
Industrial	08008902	IHR-56-277V*	Down Draft	56"	277	7000	310	0.3	16
Water and Dust Resistant Models									
Heavy Duty	08540802	HDHR-56WR	Down Draft	56"	120	7000	320	1.1	17
Heavy Duty	08540902	HDHR-60WR	Down Draft	60"	120	7800	320	0.8	21

\* 277 volt, commercial, and reversing models have lead wires instead of cordset. 36" down rod available for additional charge.

### Solid State Controls (120 & 277V Models)

MFG CATALOG NUMBER	MFG MODEL NUMBER	VOLTS	MAX AMPS	VARIABLE CONTROL KNOB	REVERSING SWITCH	MAX # OF FANS	USE WITH CEILING FAN MODEL
07976302	KBWC-13K	120	3	YES; W/3" X 5" ALUMINUM PLATE (FITS 2" X 4" OPENING)	No	1-2	CHR-56, IHR-48/56, HDHR-56/60-WR
07976402	KBWC-15	120	5			3-5	CHR-56, IHR-48/56, HDHR-56/60-WR
07994102	KBWC-110K	120	10			6-10	CHR-56, IHR-48/56, HDHR-56/60-WR
08666802	KBWC-15SK	120	5		Yes	3-5	IHR-56R
08526502	KBWC-310K	277	10		No	6-10	IHR-56-277V

### Options

MFG CATALOG NUMBER	MFG MODEL NUMBER	TYPE
08512202	HR-GUARD	FOR 56" MODELS
08504202	ADD SUFFIX; " X3"	36" DOWN ROD OPTION