

**SSN4D - 3PT SERIES ENCLOSURES
NEMA 4X 304/316L STAINLESS TWO DOOR FLOOR MOUNT**



SSN4D6248123PTA

Industry Standards

UL 508, Types 3, 4, 4X, 12 & 13
CSA Certified, Types 4, 4X & 12
NEMA/EEMAC Types 3, 4, 4X, 12 & 13

UL Files E64791

CSA File LL66078

FEATURES-SPECIFICATIONS

Applications

Designed to house electrical and electronic controls, components and instruments in wet corrosive environments. Typical applications for these enclosures include dairies, breweries, waste water, coastal, food processing and /or activities that may require hose down. Enclosures are designed for outdoor applications.

Construction

- Bodies, doors and floor stand feet are fabricated from 12/10 gauge 304 or 316L SS
- Continuously welded seams ground smooth, less knockouts or holes
- Body stiffeners added for extra strength
- Rolled lip around three sides of door and along top of enclosures opening excludes liquids and contaminants from entering

- 3PT 316L SS Padlocking Handles
- Heavy gauge continuous hinges are orivuded ti secyre doors
- Doors are removable by pulling stainless steel continuous hinge pin
- Removable print pocket is provided
- Standard 12" high floor kits are welded to bottom of enclosure
- Heavy duty removable lifting eyes
- Collar studs for mounting optional panels
- Easily removable center post permits easy panel installations
- Doors are sealed with poured in place gasket
- Grounding provisions provided

Finish

- Interior: commercial finish, Exterior: standard Wiegmann grained finish
- **Optional** back panels are white polyester powder
- **Optional** "G" panels have a conductive finish (See page I7)

Accessories

- Back panels (reference tables)
- See pages J1-J22

SSN4D 3PT SERIES TWO DOOR 3PT HANDLE STAINLESS ENCLOSURES					
CATALOG NUMBER		ENCLOSURE SIZE H X W X D	BACK PANEL CATALOG NUMBER*		BACK PANEL SIZE A X B
304 SS	316L SS		WHITE	"G"	
SSN4D6248123PT	SSN4D6248123PTA	62.06x48.06x12.06 (1576x1221x306)	NPDD6048	NPDD6048G	56.00x44.00 (1422x1118)
SSN4D6248183PT	SSN4D6248183PTA	62.06x48.06x18.06 (1576x1221x459)	NPDD6048	NPDD6048G	56.00x44.00 (1422x1118)
SSN4D6260123PT	SSN4D6260123PTA	62.06x60.06x12.06 (1576x1526x306)	NPDD6060	NPDD6060G	56.00x56.00 (1422x1422)
SSN4D7460123PT	SSN4D7460123PTA	74.06x60.06x12.06 (1881x1526x306)	NPDD7260	NPDD7260G	68.00x56.00 (1422x1422)
SSN4D7472123PT	SSN4D7472123PTA	74.06x72.06x12.06 (1881x1830x306)	NPDD7272	NPDD7272G	68.00x68.00 (1727x1727)
SSN4D7472243PT	SSN4D7472243PTA	74.06x72.06x24.06 (1881x1830x611)	NPDD7272	NPDD7272G	68.00x68.00 (1727x1727)

*Back panels must be ordered separately.