



Representative

**Catalog Number:** FPT4-4P-4C  
**Product ID:** 7TAA003440R0007  
**UPC Number:** 78599104280  
**Status:** Active

Poke-Through Base Unit, 4 Inch Drill Size, 19 Inch Length, Hub Size 1/2 Inch and 1 Inch, Galvanized Steel, with 4 20A Power Receptacles and 4 Cat-5e Data Jacks with Device Plates

- Four modular configurations for power receptacles and communications jacks mounted flush with the floor
- Full access to communications compartment through the cover without exposing power compartments even after it is installed in the floor
- Threaded conduit hubs enable all communications cabling to be enclosed in a single conduit
- Accommodates fiber optic and audio/video connectors
- Pre-wired power receptacles

### North American Specifications (UNSPSC)

UNSPSC	39121328 Fire rated poke through box
IGCC	4482 Fire rated poke through box
Brand Name	Steel City
Type	Poke Through Systems
Special Features	Four modular configurations for power receptacles and communications jacks mounted flush with the floor
Application	For above-grade, fire rated concrete floors.
Standard	UL e2969
Material	Die Cast Zinc/Galvanized Steel
Knockouts	4

### European Specifications (ETIM)

ETIM	EC000024 Installation box for underfloor-installation
Cover model	Round
Suitable for wet cleaning	N
Suitable for hollow floor	Y
Material	Other
With opening carpeting	N
Colour	Other
Length external dimension	482.6mm

### Packaging

Outer Quantity	1
Outer Dimensions (inches)	21.38x8.13x5.5
Weight Uom	7.09 lbs. Each

### Documents / Support Tools

Technical Drawing / Data Sheet	WSD-000235
Technical Drawing / Data Sheet Canada	Available on Website
Instruction Sheet	TA03724-TB2
Support/Tools	Available on Website

### Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

ABB Installation Products - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

ABB Installation Products Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)