



Representative

**Catalog Number:** 040-5233  
**Product ID:** 7TAD012280R0044  
**UPC Number:** 78621083100  
**Status:** Active

Liquidtight Connector, Straight Iron Fitting for Conduit, 3/4 Inch Flexible, Metal Conduit Connector, UL Listed Liquidtight, UL Listed As Grounding Means, Under NEC 351-9, Duraplated

**North American Specifications (UNSPSC)**

|                  |                                             |
|------------------|---------------------------------------------|
| UNSPSC           | 39121420 Liquid tight connectors            |
| IGCC             | 4585 Liquid tight connectors                |
| Brand Name       | T&B Industrial Fitting                      |
| Type             | Liquidtight Flexible Metal Conduit Fittings |
| Special Features | Dura-Plate Finish                           |
| Standard         | CSA, UL                                     |
| Size             | 3/4 Inch                                    |
| Material         | Steel                                       |

**Packaging**

|                           |                 |
|---------------------------|-----------------|
| Inner Quantity            | 25              |
| Inner Dimensions (inches) | 8x5x4           |
| Outer Quantity            | 50              |
| Outer Dimensions (inches) | 8x5x4           |
| Weight Uom                | 20 lbs. per 100 |

**Documents / Support Tools**

|                                       |                      |
|---------------------------------------|----------------------|
| Technical Drawing / Data Sheet US     | Available on Website |
| Technical Drawing / Data Sheet Canada | Available on Website |

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
www.tnb.com

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com