HUBBELL
Wiring Device-Kellems

1/2 Controlled EdgeConnect™ 20A Tamper Resistant Flat Face Gray Duplex Receptacle

By Hubbell Wiring Device-Kellems
Catalog # HBL5362STC1GYTR

1/2 Controlled EdgeConnect™ 20A Tamper Resistant Flat Face Gray Duplex Receptacle. Straight Blade Device, 2-Pole 3-Wire, 125V, Commercial Grade, Screwless Termination/Spring Terminal

Application

Spring clamp terminal strengthens over time providing a more reliable connection.

General

Catalog Number	HBL5362STC1GYTR
Color	Gray
Flammability	UL 94 V-2
Item Type	Receptacle
Material	Thermoplastic/C
Number Of Poles	2-Pole
Operating Temperature	• Maximum continuous 75 °C • Minimum (w/o impact) -40 °C
Series	EdgeConnect™
Size	3.28x1.58x1.38 in
Specifications	• Product Identification - Ratings are a permanent part of the device • Terminal Accomodation - #14 - #10AWG Wire (Solid or Stranded) Copper or UL listed CCA conductors only • Terminal Identification - Terminals Identified in Accordance with UL 498 and CSA
Style	Flat Face
Type	Controlled
UPC	783585757261

Electrical Ratings

Current Rating	20 A
Dielectric Strength	Withstands 2,000V minimum
Voltage Rating	125 V

Conductor Related

Number Of Wires	3-Wire

Certifications And Compliance

Industry Standard(s)	• UL Listed to UL498 File No. E2186 • Certified to CSA 22.2, No. 42 File 285 • Fed. Spec. W-C-596 • NEMA® WD-6 Compliant
Nema Rating	5-20R

Logistics

Carton Quantity	10

Product Assets

Installation Manuals - HUBBELL EdgeConnect™ SCREWLESS TERMINATION RECEPTACLES Installation Instructions
Literature - EdgeConnect™ Technology
Specifications - HBL5362STC1GYTR
Warranty - Industrial & Commercial Products
Video - Hubbell® EdgeConnect™ Technology

©2025 Hubbell Incorporated. All rights reserved