SUPPORT GRIPS STANDARD DUTY, SPLIT ROD

FR175U | Pass & Seymour

FEATURES & BENEFITS

Standard duty, Split rod, Single eye. Cable diameter - 1.750-1.990", Bale length - 14", Mesh length - 20", Break strength - 2,640.

- Split rod support grips are designed for loads up to 600 lbs.
- Vertical runs of no more than 100 ft.
- They are available in a variety of eye styles and cable ranges for supporting electrical and fiber optic cable, metal rods, and tubing.
- Split rod support grips are used when the end of the cable cannot be easily accessed and the installation is temporary.
- Support grips are woven of corrosion-resistant tinned-bronze wire.

SPECIFICATIONS

GENERAL INFO

Typical Applications: Service Drop, Standard
Type: Standard Split Rod
Duty: Standard Duty
Special Features: Single Eye

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

CSA Listing Info: No
CUL Listing No: No
cULus: No
cURus: No
Federal Spec: No
UL Listing No: No
UN SPSC: 39121722
UR: No

DIMENSIONS

Diameter (US): 6.5"
Weight: 0.4234

TECHNICAL INFORMATION

NPT Size: 1.750"-1.990"

BUY AMERICAN ACT COMPLIANCE

Country Of Origin: MEXICO
Buy American Act Status: Trade Agreement Act Compliant