

GREER

Ceiling mounted • Dry location listed

Description:

This five-blade 54" Greer ceiling fan complements either industrial or farmhouse decor. It comes with a wire meshed shade light kit that uses two vintage LED lamps (Included) and remote control with batteries are also included. Hang it on a flat or sloped ceiling with its dual mount system. Can be used to comply with California Title 20.

Specifications:

- Gilded Iron (-71) (Painted)
- Steel construction
- 54" Greer indoor ceiling fan features five blades and an LED light source, offering both form and function with energy- and cost-savings benefits
- Wire meshed shade light kit included that uses two vintage LED lamps (included)
- Features reversible Walnut/Driftwood blades and a Gilded Iron finish
- A hand held remote control with fan speed control and full range light dimming is included and comes with a convenient wall bracket for storage
- Remote control may be replaced by a P2630-30 wall control
- The five-blade Greer fan features a dual mount system to offer greater flexibility when installing
- The fan can be installed on a flat or sloped ceiling
- Reversible motor for year round comfort allows you to choose either a down draft (summer) or an up draft (winter)
- As a general rule of thumb, lighting experts suggest this fan is ideal in a room size that ranges from 226- to 400-square feet
- A 3/4" x 6" downrod is included. Longer accessory downrods can be ordered separately
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 80" of wire supplied
- Walnut/Driftwood reversible blades, plywood construction
- 12 degree blade pitch
- Full Function Remote Included
- Triple capacitor speed control, manual reverse control
- Airflow: 4794 CFM*
- Energy consumption: 64 watts (excluding lights)*
- Airflow efficiency: 75 cfm/watt*
- * Fan on a downrod

Performance:

Number of Modules	2
Input Power	6.5w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	900/69 (LM-79) per module
CCT	2200 K
CRI	90 CRI
Life (hours)	15,000 (L70/TM-21)
EMI/RFI	Title 20
Min. Start Temp	-10 °C
Max. Operating Temp	40 °C
Warranty	Limited Lifetime warranty
Labels	UL Dry location listed

P2584-71


Images:



Dimensions:

Diameter: 54"

Height: 20"



P2584-71**Dimming Notes:**

P2584 is designed to be compatible with many controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

"Lutron - NTEVL-300

Lutron - DVELV-300P

Lutron - Caseta Wireless

Leviton – 6672

Leviton – 6674

Lutron - AYCL-153P

Lutron - AYLV-600P

Lutron - MAELV-601

Leviton - AWRMG-EAW"

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.