

Flush Mount Linear LED

Ceiling mounted • Damp location listed **PROGRESS LED**


Description:

LED Linear Cloud features an LED light source, offering both form and function with energy- and cost-savings benefits. The LED Linear Cloud can be used in kitchens, basements, garages and many other utility areas. It has a white contoured shallow acrylic cloud lens with Urban Bronze finish end caps. The LED Linear Cloud is a ceiling mount fixture that delivers 3,676 lumens, is 90 CRI and with 3000K color temperature. Acrylic diffuser gives even light distribution. ENERGY STAR certified, Title 24 compliant, Damp location listed. Flicker-free dimming to 10% brightness with most Forward Phase (Triac) dimmers.

Specifications:


- Urban Bronze (-174) (plated)
- Steel construction
- White acrylic diffuser
- LED Linear Cloud
- Features an LED light source, offering both form and function with energy- and cost-savings benefits
- The LED Linear Cloud can be used in kitchens, basements, garages and many other utility areas
- White contoured shallow acrylic cloud lens
- The LED Linear Cloud is a ceiling mount fixture
- 53W LED module offers 71 lumens per watt
- 3,676 lumens, 90 CRI and 3000K color temperature
- Acrylic diffuser for even light distribution
- Measures 4 1/2" H x 11 3/4" W x 48-5/16" L
- Damp location listed
- Mounting for outlet box included
- Canopy covers standard 4 hexagonal outlet box
- Flicker-free dimming to 10% brightness with most Forward Phase (Triac) dimmers
- 5-year warranty
- Dimmable to 10% brightness (See Dimming Notes)
- ENERGY STAR® qualified
- Meets California Title 24 high efficacy requirements

Performance:

Number of Modules	1
Input Power	52w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	3676/71 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	54,000 (L70/TM-21)
FCC	
Min. Start Temp	-30 °C
Max. Operating Temp	
Warranty	5 year warranty
Labels	cETLus Damp location listed
	ENERGY STAR® qualified
	Meets California Title 24 high efficacy requirements

P7258-17430K9

Images:



Dimensions:

Diameter: Width: 11-13/16"

Height: 4-1/2"

P7258-17430K9

Dimming Notes:

P7258 is designed to be compatible with many Triac/Forward Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron DVCL-153P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.