

96010

UPC: 08593796010
 UNSPSC: 31201606
 Standard Qty: 1
 Master Carton Qty: 24
 Country of Origin: USA

Wet Patch Roof Cement, 10.3 oz Tube



Product Attributes

Brand Name	Minerallac
Sub Brand	Cully
Type	Wet Patch Roof Cement
Special Features	Patches roof leaks on wet or dry surfaces. Heavy-bodied—spreads easily. Forms a tough flexible film. Doesn't run, sag, crack, or peel.
Application	Repairs holes, cracks, and splits on asphalt coated, composition, and metal roofs. Seals metal joints and flashings at parapet walls, chimneys, skylights, vent pipes, etc.. Seals tabs of asphalt shingles.
Color	Black
Size	10.3
Specific Gravity	1.01
Coverage	12-1/2 sq. ft. per gallon applied 1/8" thick.
Flash Point	105 °F
Container	Tube
Sub Brand	Cully
Sub Brand	Cully
Type	Wet Patch Leak Repair
Type	Wet Patch Leak Repair
Application	Leak repair sealant that stops leaks instantly on wet or dry surfaces
Features	Stops leaks instantly, even in standing water, apply from 20 F -120 F degrees, 100% wet surface adhesion per ASTM D3409, No blistering, sagging or sliding per ASTM D4586
Compliance	Miami-Dade County Approved, Meets or exceeds ASTM D3409 (Standard Test Method for adhesion of asphalt-roof cement to damp, wet, or underwater surfaces), Meets or exceeds ASTM D4586 (Standard Specification for Asphalt Roof Cement)

Compliance Information

Buy America Act Compliant: Yes
 Buy American Act Compliant: Yes
 RoHS Compliant: No
 UL Compliant:
 UL Code:

Proposition 65



☐ WARNING: This product can expose you to Asphalt impurities, which is known to the State of California to cause cancer and reproductive harm. For more information go to www.P65Warnings.ca.gov.

Minerallac Company

Tel: 800-927-3293
 Fax: 800-824-8942
www.minerallac.com

96010

UPC: 08593796010
 UNSPSC: 31201606
 Standard Qty: 1
 Master Carton Qty: 24
 Country of Origin: USA

Wet Patch Roof Cement, 10.3 oz Tube



Features	Stops leaks instantly, even in standing water, apply from 20 F -120 F degrees, 100% wet surface adhesion per ASTM D3409, No blistering, sagging or sliding per ASTM D4586
Size	11 fl oz Cartidge
Size	11 fl oz Cartidge

WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.