

Product Specification Sheet

94434

UPC: 08593794434

UNSPSC: 31201519

Standard Qty: 1

Master Carton Qty: 24

Country of Origin: TAIWAN

2" x 100' UPC Approved Printed PVC Pipe Wrap; 10 Mil



Pi	roduct Attributes	Compliance Information
Brand Name	Minerallac	Buy America Act Compliant: No
Sub Brand	Cully	
Туре	Pipe Wrap	Buy American Act Compliant: No
Special Features	Anti-corrosive and moisture resistant	RoHS Compliant: No
Application	Perfect for industrial identification, color coding, and pipe wrapping purposes.	UL Compliant:
Material	Rubber-based, pressure sensitive adhesive system	UL Code:
Color	Black	Proposition 65
Length	100'	1 Toposition 65
Width	2"	□ WARNING: This product can expose you to DEHP, which is known to the State of California to cause cancer and reproductive harm. For more information go to www.P65Warnings.ca.gov.
Thickness	10	
Special Features	Designed to protect external pipe surfaces from corrosion. Printed with UPC shield for quick code recognition. Pliable, easy to apply. Ideally suited for valves, elbows, and fittings,	
Application	both in plants and outdoors. Provides outstanding protection against sunlight, weather, acids, alkalies, saltwater, aging, and corrosive salts and fumes.	
Standard	General Purpose; UPC Approved	Minerallac Company
Material	Polyvinyl Chloride (PVC) Tape	Tel: 800-927-3293
Length	100	Fax: 800-824-8942
Width	2	www.minerallac.com
Tensile Strength	20 lb/in	
Thickness	10.0	
Temperature Range	-20°F to +176°F	
Backing Material	Pressure Sensitive Adhesive	
Backing Material	Pressure-Sensitive Adhesive	
Width	2 in	
Length	100 ft	
Thickness	10.0 mil	













Product Specification Sheet

94434

UPC: 08593794434

UNSPSC: 31201519

Standard Qty: 1

Master Carton Qty: 24

Country of Origin: TAIWAN

2" x 100' UPC Approved Printed PVC Pipe Wrap; 10 Mil



Special Features	Soft PVC coated with a rubber-based pressure sensitive adhesive system, Winmore Pipe Wrap Tape is perfect for industrial identification, color coding, and pipe wrapping purposes. Our tape is suitable for use up to 140 F, and is anti-corrosive and moisture resistant. The tape is UL rated
Standard	General Purpose; UL Rated
Standard	General Purpose; UL Rated
Material	Soft Polyvinyl Chloride (PVC) Tape

WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.









