

96242

UPC: 08593796242
 UNSPSC: 46191503
 Standard Qty: 1
 Master Carton Qty: 50
 Country of Origin: USA

Firestop Gaskets Single Switch, 1ct



Product Attributes

Brand Name	Minerallac
Sub Brand	Cully
Type	Fire Shield
Special Features	Highly Intumescent Material
Application	Applied by hand
Color	Silver
Size	Single Switch
Sub Brand	Cully
Type	Firerated gasket
Description	is a single component fire rated gasket for use with electrical boxes when addressing steel electrical box penetrations in fire rated assemblies. It is mounted on the inside of the cover plate and installed at the same time as the cover plate, covering the opening and providing the necessary fire protection. When exposed to heat, the gaskets highly intumescent nature causes it to expand forming a char that will seal off the opening and prevent the spread of flames and limit the temperature rise on the unexposed surface.
Application	Firestop gaskets are used when electrical boxes are installed in rated walls facing opposite directions and horizontally separated by less than 24". UL tested and can used with both metal and plastica cover plates.
Characteristics/ Features	Good sound insulator, easy to install, highly intumescent, STC rating 54, complies to UL required accelerated aging and high humidity testing, VOC compliant-CDPH standard method v1.2, Tested in accordance with UL 263/ ASTM E119 and ASTM E814 (UL 1479)
Size	5 x 5 x 5 (Single Switch)

Compliance Information

Buy America Act Compliant: No
 Buy American Act Compliant: No
 RoHS Compliant: No
 UL Compliant:
 UL Code:

Proposition 65

This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.

Minerallac Company

Tel: 800-927-3293
 Fax: 800-824-8942
www.minerallac.com

96242

UPC: 08593796242

UNSPSC: 46191503

Standard Qty: 1

Master Carton Qty: 50

Country of Origin: USA

Firestop Gaskets Single Switch, 1ct



WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.