

96062

UPC: 08593796062

UNSPSC: 46191503

Standard Qty: 1

Master Carton Qty: 12

Country of Origin: USA

FireStop Caulk 150+, 10.3 oz, 1ct Cartridge Tube



Product Attributes

Brand Name	Minerallac
Sub Brand	Cully
Type	General-Purpose Firestop Sealant
Special Features	Non-sag caulking grade sealant that is easy to apply as well as retrofit. Can be used in areas with some movement.
Application	General-purpose fire-rated sealant and smoke seal for construction joints and through-penetrations on both horizontal and vertical surfaces.
Color	Red
Size	10.3
Temperature Range	40-120 Degrees Fahrenheit
Specific Gravity	1.25
Container	Tube
Base Content	Water
Functional Cure	3-4 Weeks (at 77 Degrees Fahrenheit)
Flash Point	None
Sub Brand	Cully
Type	Firestop Sealants
Description	General purpose fire rated sealant, acoustic sealant, and smoke seal for construction joints and through-penetrations. 150+ is a water based, non-sag caulking grade sealant that is easy to apply as well as retrofit.

Compliance Information

Buy America Act Compliant: No

Buy American Act Compliant: No

RoHS Compliant: No

UL Compliant:

UL Code:

Proposition 65

This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.

Minerallac Company

Tel: 800-927-3293

Fax: 800-824-8942

www.minerallac.com

96062

UPC: 08593796062
 UNSPSC: 46191503
 Standard Qty: 1
 Master Carton Qty: 12
 Country of Origin: USA

FireStop Caulk 150+, 10.3 oz, 1ct Cartridge Tube



Application	Metacaulk 1000 can be used in interior applications as a general purpose fire rated sealant and smoke seal for construction joints, through penetrations and blank openings on both vertical and horizontal surfaces. Use Metacaulk 1000 to prevenet the spread of fire and smoke through joints in fire rated gypsum wallboard partitions, concrete block or concrete walls and/ or concrete or corrugated steel deck floor/ ceiling assemblies.
Size	10.3 oz cartridge
Characteristics/ Features	Water based, excellent freeze-thaw, flexible set, paintable, VOC compliant, safe and easy to use, STC rating 65

WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.