

Product Specification Sheet

96055

UPC: 08593796055

UNSPSC: 46191503

Standard Qty: 1

Master Carton Qty: 12

Country of Origin: USA

FireStop Caulk 1000+, 10.3 oz, 1ct Cartridge Tube



Product Attributes		Compliance Information
Brand Name	Minerallac	Buy America Act Compliant: No
Sub Brand	Cully	Buy America Act Compliant. No
Flash Point	None	Buy American Act Compliant: No
Туре	Firestop Sealant	RoHS Compliant: No
Special Features	Highly Intumescent. Non-sagging. Non-toxic. No VOC's.	UL Compliant:
Application	For use in fire-rated gypsum wallboard partitions, concrete walls or floors, wood floors and concrete or corrugated steel deck floor/ceiling	UL Code:
	assemblies.	Proposition 65
Size	10.3	This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.
Container	Tube	
Specific Gravity	1.25	
Sub Brand	Cully	
Size	10.3 oz cartridge	
Size	10.3 oz cartridge	
Characteristics/ Features	Water based, excellent freeze-thaw, flexible set, highly intumescent, paintable, VOC compliant, safe and easy to use, 3 year shelf life	Minaralla a Carra
Color	Red	Minerallac Company
	Metacaulk 1000 can be used in interior applications as a general purpose fire rated sealant and smoke seal for construction joints, through penetrations and blank openings on both vertical and horizontal surfaces. Use	Tel: 800-927-3293 Fax: 800-824-8942 www.minerallac.com
Applications	Metacaulk 1000 to prevenet the spread of fire and smoke through joints in fire rated gypsum wallboard partitions, concrete block or concrete walls and/ or concrete or corrugated steel deck floor/ ceiling assemblies.	









Product Specification Sheet

96055

UPC: 08593796055

UNSPSC: 46191503

Standard Qty: 1

Master Carton Qty: 12

Description

Country of Origin: USA

FireStop Caulk 1000+, 10.3 oz, 1ct Cartridge Tube

Metacaulk 1000 is a single component, general purpose fire rated sealant and smoke seal for

construction joints and through-penetrations. In the event of a fire, Metacaulk 1000 will prevenet

the spread of flames, smoke, hot gases and water through joint openings and through-

penetration.



WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence,

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.











