

94396


UPC: 08593794396

UNSPSC: 31201501

Standard Qty: 1

Master Carton Qty: 24

Country of Origin: USA



CULLY GENERAL 9MIL DUCT TAPE; 2" x 60 Yd. Silver Duct Tape; General Purpose; Cloth Laminate

Product Attributes

Brand Name	Minerallac
Sub Brand	Cully
Type	Duct Tape
Special Features	Enhanced adhesion allows for great versatility.
Color	Silver
Length	60
Width	2"
Thickness	9
Tensile Strength	23
Special Features	Aggressive adhesive and moderately strong backing enable suitability for a wide range of applications. Tested in accordance with UL 723.
Application	Maintenance and General Repair; General Purpose Abatement and Contractor Applications; Bundling, Patching, and Mending; Heavy-Duty Box Sealing
Standard	General Purpose Use
Material	Polyethylene Coated Cloth
Width	2
Tensile Strength	24
Thickness	9.0
Temperature Range	40°F to 200°F Operating Temperature
Tensile Strength	24
Backing Material	Polyethylene Coated Cloth / Natural Rubber Adhesive
Backing Material	Polyethylene Coated Cloth / Natural Rubber Adhesive
Adhesion Strength	70
Adhesion Strength	70

Compliance Information

Buy America Act Compliant: No

Buy American Act Compliant: No

RoHS Compliant: No

UL Compliant:

UL Code:

Proposition 65

This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.

Minerallac Company

Tel: 800-927-3293
Fax: 800-824-8942
www.minerallac.com

94396

UPC: 08593794396

UNSPSC: 31201501

Standard Qty: 1

Master Carton Qty: 24

Country of Origin: USA



CULLY GENERAL 9MIL DUCT TAPE; 2" x 60 Yd. Silver Duct Tape; General Purpose; Cloth Laminate

WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.