

94325

UPC: 08593794325

UNSPSC: 31201502

Standard Qty: 1

Master Carton Qty: 10

Country of Origin: USA



3/4" x 22' Rubber Splicing Tape; Black/Blue Liner

Product Attributes

Brand Name	Minerallac
Sub Brand	Cully
Type	General Purpose Vinyl
Application	Provides moisture-tight electrical and mechanical protection
Material	Vinyl
Color	Black
Size	3/4"
Length	22'
Width	0.750"
Temperature Range	0°C to 80°C
Type	Rubber Splicing Tape
Special Features	Meets Requirements of ASTM D-119 and HH-I-553C, Grade B, UL510 Listing # 2C58.
Application	Insulates electrical connections up to 600V; Seals out moisture from low-voltage connections; Insulates service drops and lighting connections; Provides moisture-tight electrical and mechanical protection
Standard	Self-Fusing Rubber Tape
Material	Low Voltage Un-Vulcanized Rubber
Color	Black/Blue Liner
Size	3/4
Length	22
Width	0.750
Tensile Strength	275 psi (UL510)
Thickness	30 mil
Temperature Range	0°C to 80°C (1768°F)
Maximum Voltage	14.6 Breakdown Voltage
Resists	Bleach, Steam, Saltwater, Oils, Detergents, and Other Chemicals

Compliance Information

Buy America Act Compliant: No

Buy American Act Compliant: No

RoHS Compliant: No

UL Compliant:

UL Code:

Proposition 65

This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.

Minerallac Company

Tel: 800-927-3293

Fax: 800-824-8942

www.minerallac.com

94325

UPC: 08593794325

UNSPSC: 31201502

Standard Qty: 1

Master Carton Qty: 10

Country of Origin: USA



3/4" x 22' Rubber Splicing Tape; Black/Blue Liner

WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.