

A60Q Amp-Trap® Form 101 high speed fuses feature the only 600V AC / DC rating in the industry of similar size $(1-1/2" \times 13/32")$ fuses protecting semiconductors. A60Q also has the lowest I2t of all similar fuses and excellent cycling ability. Applications include inverters and small equipment requiring extremely fast response to faults, without the need to carry sustained heavy overloads.

FEATURES/BENEFITS


- Lowest I2t of any fuse this size for greater protection
- Excellent cycling ability gives advantage in equipment design
- 600V AC / DC rated

Catalog Numbering System					
A	60	0	30	- 2	
Amp-Trap® Fuse	Rated Volts - 600	Style	Amperes*	Mounting Types* Ferrule, midget dims. [1½" x 13/32"]: 2	

* For ampere ratings and styles not listed, call Technical Services at 978-248-8914.

CATALOG NUMBERS (AMPS)

A60Q5-2	A60Q12-2	A60Q30-2
A60Q6-2	A60Q15-2	A60Q35-2
A60Q8-2	A60Q20-2	A60Q40-2
A60Q10-2	A60Q25-2	



RATINGS

- Volts: 600VAC/DC
- Amps: 5 to 40A (AC); 5 to 40A (DC)
- I.R.: 200kA I.R. AC, 100kA I.R. DC
- L/R: 10ms

HIGHLIGHTS

- 600VAC/DC rated
- Extremely fast acting
- Current limiting
- Lowest I²t
- · Excellent cycling ability

APPLICATIONS

 Protection of small inverters and drives, and equipment requiring the highest degree of protection

APPROVALS/STANDARDS

 UL Recognized component



- AC: UL guide JFHR2 File E60314
- DC: UL file E60314

FUSE HOLDERS FOR A60Q FUSES

UltraSafe™ **USM Series**

Fuse Holders

303 Series

Midget Fuse

Blocks