

Specifications



Eaton XTMF9A00C

Eaton XT IEC mini contactor, 8.80A, 415 Vac, 50 Hz, 480 Vac, 60 Hz, ONO-ONC, 20A, 45 mm mini, 50-60 Hz, Four-pole, Non-reversing, XT IEC series, Screw terminals, Full voltage non-reversing mini contactor



General specifications

PRODUCT NAME	Eaton XT IEC mini contactor
CATALOG NUMBER	XTMF9A00C
EAN	4015080518075
PRODUCT LENGTH/DEPTH	2 in
PRODUCT HEIGHT	1.5 in
PRODUCT WIDTH	2 in
PRODUCT WEIGHT	0.4 lb
CERTIFICATIONS	UL Listed CSA Certified EN 60947 IEC 60947



Powering Business Worldwide

Product specifications

AMPERAGE RATING	8.80A
NUMBER OF POLES	Four-pole
TYPE	Full voltage non-reversing mini contactor
FREQUENCY RATING	50-60 Hz
FRAME SIZE	45 mm - mini
TERMINALS	Screw terminals
COIL	415-480 Vac, 50/60 Hz
COIL VOLTAGE	415-480 Vac, 50/60 Hz
CONTACT CONFIGURATION	0 NO, 0 NC
CONTINUOUS AMPERE RATING	20 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
MULTIMEDIA	S1. E4. Ask the Experts - NEMA, IEC and DP contactors Contactors Explained
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTMF9A00C

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

