

Product data sheet

Specifications



Auxiliary contacts, TeSys GS, 2NC +2NO, instantaneous, left side mounting, for GS2 with front handle test position

GS1ANT2

⚠ Discontinued on: Jan 31, 2024

⚠ Discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	TeSys
Device short name	GS1AN
Product or Component Type	Auxiliary contact
Contact application	O, I and test position signalling
Contacts type and composition	2 NO + 2 NC
Contact operation	Instantaneous
[I _{th}] conventional free air thermal current	20 A (at 104 °F (40 °C))
[I _e] rated operational current	1 A 220 V DC-13 10 A 230 V AC-15 12 A 127 V AC-15 4 A 48 V DC-13 6 A 440 V AC-15 8 A 400/415 V AC-15 1.2 A 110 V DC-13

Complementary

Range compatibility	TeSys TeSys GS fuse-switch disconnectors
Mechanical durability	30000 cycles
Electrical durability	30000 cycles AC-15
switch rated current	50 A 63 A 125 A 315 A 100 A 250 A 60 A 200 A 160 A 400 A
Fuse type	DIN BS NFC
Type of operating handle	External frontal
Product Weight	0.569 lb(US) (0.258 kg)

Ordering and shipping details

Category	US10I1122640
----------	--------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Discount Schedule	0111
GTIN	3389110255218
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.38 in (3.5 cm)
Package 1 Width	2.76 in (7.0 cm)
Package 1 Length	5.12 in (13.0 cm)
Package 1 Weight	9.1 oz (258.0 g)
Unit Type of Package 2	S01
Number of Units in Package 2	12
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	5.91 in (15.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	7.339 lb(US) (3.329 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant

California proposition 65

WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture

[Circularity Profile](#)

[End of Life Information](#)