

Siemens Low Voltage Molded Case Circuit Breakers Panelboard Mounting 480V Circuit Breakers - 1-pole, TM - BQD, 14KAIC, 277VAC are Circuit Protection Molded Case Circuit Breakers. Type: BQD Features: PANELBOARD MOUNT Application: CONSTRUCTION Std: UL 489 CSA-C22.2 IEC 60947-2 V. Rating: 277V A. Rating: 25A F. Rating: 50/60HZ Frame: 100A Trip Type: THERMAL MAGNETIC TRIP UNIT Interrupt Rating: 14KA No. Of Poles: 1P Connection: LOW TAB Material: MOLDED CASE CIRCUIT BREAKER L: 3 W: 1

product function note	
number of poles	1
suitability for operation	CONSTRUCTION
Electricity	
continuous current rated value	25 A
supply voltage frequency rated value 50/60 Hz	Yes
Environmental conditions	
ambient temperature during operation maximum	40 °C
Model	
product brand name	Siemens
special product feature	PANELBOARD MOUNT
type of electrical connection	LOW TAB
Mechanical Design	
depth [in]	3 in
design of the overload release	THERMAL MAGNETIC TRIP UNIT
design of the product	BQD
height [in]	5 in
material of the enclosure	MOLDED CASE CIRCUIT BREAKER
size of the circuit-breaker	100A
width [in]	1 in
General product approval	
standard	UL 489 CSA-C22.2 IEC 60947-2

last modified:

12/20/2023 

