Product data sheet Characteristics

8536SGO1V02S

NEMA Motor Starter, Type S, nonreversing, Size 5, 270A, 200 HP at 460 VAC, 3 phase, 3 pole, melting alloy, 120 VAC coil, open, 10 kA SSCR

Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

o o mpromornary		
NEMA Size	5	
Rated Current	270 A	
Number of Poles	3P	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	Melting alloy 3	
Horsepower Rating	75 HP 200 V AC 100 HP 230 V AC 200 HP 460 V AC 200 HP 575 V AC	
SCCR	Circuit-breaker: 10 kA at 600 V AC Fuse: 10 kA at 600 V AC	
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz	
Control Circuit Type	Separate control circuit	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Terminal Type	Screw clamp terminals	
Height	17.56 in (446.02 mm)	
Width	8.56 in (217.42 mm)	
Depth	8.75 in (222.25 mm)	

Environment

Enclosure Type	Not rated (open device)
Certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21194 - 8502,36SG(NOT S*R,S*T,S*W)
Discount Schedule	CP1
GTIN	00785901854821
Nbr. of units in pkg.	1
Package weight(Lbs)	55.9 lb(US) (25.36 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	10.30 in (26.162 cm)
Package 1 width	11.00 in (27.940 cm)
Package 1 Length	19.80 in (50.292 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	☐ China RoHS Declaration

Contractual warranty

· · · · · · · · · · · · · · · · · · ·		
Warranty	18 months	