



## Main

Product	Double Throw Safety Switch
Current Rating	200 A
Certifications	UL Listed
Enclosure Rating	NEMA 1 steel
Factory Installed Neutral	Neutral (factory installed)
Disconnect Type	Non-fusible disconnect switch
Mounting Type	Surface
Number of Poles	3
Voltage Rating	480 V AC 250 V DC
Wire Size	AWG 6...300 kcmil copper or aluminium

## Complementary

Maximum Horse Power Rating	15 hp 480 V AC 3 phase NEC 240.6
Width	23.88 in (606.55 mm)
Height	30.88 in (784.35 mm)
Maximum Depth	11.75 in (298.45 mm)
Tightening torque	340 lbf.in (38.41 N.m) AWG 6...300 kcmil

## Ordering and shipping details

Category	00033 - DT SWITCH,NEMA1
Discount Schedule	DE1
GTIN	00785901119395
Nbr. of units in pkg.	1
Package weight(Lbs)	63.5 lb(US) (28.80 kg)
Returnability	No
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

---

Warranty

18 months

---