

Product data sheet

Characteristics

8910DP41V14

Contactor, Definite Purpose, 40A, 1 pole, 24/24 VAC 50/60 Hz coil, open



Main

Product or component type	Definite Purpose Contactor
Line Rated Current	40 A
Number of Poles	1P
Pole contact composition	1 NO
Range of product	DP

Complementary

Maximum Horse Power Rating	2 Hp 115 V AC, 1 phase 5 hp 230 V AC, 1 phase
Locked rotor rated current	240 A 277 V AC 200 A 460 V AC 160 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	24 V AC 50/60 Hz
Phase	1 phase
Electrical connection	Quick connect terminals Box lugs

Environment

Product certifications	UL Recognized CSA
------------------------	----------------------

Ordering and shipping details

Category	21357 - 8910 DP41
Discount Schedule	CP1B
GTIN	00785901233053
Nbr. of units in pkg.	1
Package weight(Lbs)	0.51 lb(US) (0.23 kg)
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.30 in (5.842 cm)
Package 1 width	2.60 in (6.604 cm)
Package 1 Length	3.40 in (8.636 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	12
Package 2 Weight	6.44 lb(US) (2.921 kg)
Package 2 Height	5.90 in (14.986 cm)
Package 2 width	7.20 in (18.288 cm)
Package 2 Length	7.20 in (18.288 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------