

# Product data sheet

## Characteristics

# 9070T5000D31

Transformer, Type T, industrial control, 5000 VA, 240/480 VAC pri / 120/240 VAC second, 1 phase, 50/60 Hz, 115 °C rise



### Main

Product Type	Industrial Control Transformer
Power Rating	5000 VA
Type	T

### Complementary

Number of Phases	1 phase
Power Rating	5000 VA UL 5000 VA CSA 5000 VA NOM 3000 VA
Temperature Rise	115 °C
Electrical Connection	Screw clamp terminals
Height	8.75 in (222.25 mm)
Width	9 in (228.60 mm)
Depth	9.15 in (232.41 mm)
Material	Copper winding
Fingersafe Cover Compatibility	FSC2

### Environment

Certifications	CSA file LR37055 guide 184-N-90 UL listed file E61239
Enclosure Type	Not rated (open device)
Insulation Temperature	356 °F (180 °C)

### Ordering and shipping details

Category	16205 - 9070 T (NOT TF) 3000 - 5000VA
Discount Schedule	CP8
GTIN	00785901776659
Nbr. of units in pkg.	1
Package weight(Lbs)	93.8 lb(US) (42.55 kg)
Returnability	No
Country of origin	US

### Packing Units

Package 1 Height	13.20 in (33.528 cm)
Package 1 width	11.80 in (29.972 cm)
Package 1 Length	14.80 in (37.592 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	10 Years
----------	----------